



All dimensions are in mm; tolerances acc. ISO 2768 m-H

Interface

According to

MIL-STD-348A, Fig. 326

Documents

PCB layout

B 120

Tape & reel packaging

VG28.01M00

Material and plating

Connector parts

Center contact

Material

Brass

Outer contact

Brass

Dielectric

LCP

Plating

AuroDur®, gold plated

AuroDur®, gold plated

Electrical data

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 26.5 GHz |
| Return loss | ≥ 26 dB, DC to 6 GHz ≥ 20 dB, 6 to 12 GHz |
| Insertion loss | $\leq 0.05 \times \sqrt{f(\text{GHz})}$ dB |
| Insulation resistance | ≥ 5 G Ω |
| Center contact resistance | ≤ 6.0 m Ω |
| Outer contact resistance | ≤ 2.0 m Ω |
| Test voltage | 500 V rms |
| Working voltage | 335 V rms |
| Contact Current | 1.2A DC max. |

- VSWR in application depends decisive on PCB layout -

Mechanical data

| | |
|----------------------------|------------|
| Mating cycles | ≥ 500 |
| Center contact captivation | ≥ 7 N |
| Engagement force | |
| - limited detent | 45 N max. |
| Disengagement force | |
| - limited detent | 9 N min. |

Environmental data

| | |
|----------------------------|--------------------------------------|
| Temperature range | -65°C to +155°C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition A |
| Moisture resistance | MIL-STD-202, Method 106 |
| Max. soldering temperature | IEC 61760-1, +260°C for 10 sec. |
| RoHS | compliant |

Tooling

N/A

Suitable cables

N/A

Weight

Weight 0.3 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|----------|----------|-------------------|----------|------|---------------------------|-----------|----------|
| A. König | 10/07/07 | Sa. Krautenbacher | 12.03.14 | c00 | 14-0352 | T. Krojer | 12.03.14 |

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel.: +49 8684 18-0
Fax: +49 8684 18-499
email: info@rosenberger.de

Page
2 / 2