

## Coupler connector - CA-17S1N8A9007 - 1620050

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling connector, straight, shielded: Yes, SPEEDCON locking, M23, Number of positions: 17, Type of contact: Socket, Crimp connection, Cable diameter: 6 mm ... 10 mm

The figure shows the 12-pos. product version

### Product Features



### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85366990 |
| Country of origin    | Germany  |

### Technical data

#### Temperature range

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### Data of the insulating body

|                                                    |                                                          |
|----------------------------------------------------|----------------------------------------------------------|
| Note                                               | Order information Order crimp contacts Ø 1 mm separately |
| Insulator material                                 | PA 66                                                    |
| Direction of rotation of contact chamber numbering | Standard                                                 |
| Coding                                             | N                                                        |
| Contact connection method                          | Crimp connection                                         |
| Type of contacts                                   | Socket                                                   |
| Number of positions                                | 17                                                       |
| Contact diameter of power contacts                 | 1 mm                                                     |
| Nominal current per power contact at 25°C          | 8 A                                                      |
| Nominal voltage, power contact                     | 150 V                                                    |
| Surge voltage category                             | II                                                       |

## Coupler connector - CA-17S1N8A9007 - 1620050

### Technical data

#### Data of the insulating body

|                  |   |
|------------------|---|
| Pollution degree | 3 |
|------------------|---|

#### Housing data

|                                        |                                                                      |
|----------------------------------------|----------------------------------------------------------------------|
| Housing material                       | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking                        | SPEEDCON locking                                                     |
| Degree of protection (when plugged in) | IP67                                                                 |
| Thread type                            | M23                                                                  |

#### Cable seal data

|                     |       |
|---------------------|-------|
| Min. cable diameter | 6 mm  |
| Max. cable diameter | 10 mm |
| Sealing material    | NBR   |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 272607xx |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260702 |
| eCl@ss 7.0 | 27440102 |
| eCl@ss 8.0 | 27440102 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |

### Approvals

#### Approvals

## Coupler connector - CA-17S1N8A9007 - 1620050

### Approvals

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

#### Approvals submitted

#### Approval details

|                                                                                                 |       |
|-------------------------------------------------------------------------------------------------|-------|
| UL Recognized  |       |
|                                                                                                 |       |
| mm²/AWG/kcmil                                                                                   | 20    |
| Nominal current I <sub>N</sub>                                                                  | 5 A   |
| Nominal voltage U <sub>N</sub>                                                                  | 150 V |


|                                                                                                    |       |
|----------------------------------------------------------------------------------------------------|-------|
| cUL Recognized  |       |
|                                                                                                    |       |
| mm²/AWG/kcmil                                                                                      | 20    |
| Nominal current I <sub>N</sub>                                                                     | 3 A   |
| Nominal voltage U <sub>N</sub>                                                                     | 150 V |

|                                                                                                      |  |
|------------------------------------------------------------------------------------------------------|--|
| cULus Recognized  |  |
|------------------------------------------------------------------------------------------------------|--|

### Drawings

## Coupler connector - CA-17S1N8A9007 - 1620050

Schematic diagram



Dimensional drawing

