

## Coaxial Cable Connector 11\_QMA-50-2-1/133\_N

### Description

Straight cable plug

Interface standards  
QMA QLF compliant



### Technical Data

#### Electrical Data

|                          |        |
|--------------------------|--------|
| Impedance                | 50 Ω   |
| Interface frequency max. | 18 GHz |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | crimped   |
| Outer contact  | crimped   |
| Weight         | 0.0041 kg |

#### Environmental Data

|  |                 |
|--|-----------------|
| Operating temperature                                | -40 °C to 85 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant       |

#### Material Data

| Piece Parts    | Material   | Surface Plating       |
|----------------|------------|-----------------------|
| Centre contact | Brass      | SUCOPRO Plating       |
| Outer contact  | Bronze     | SUCOPLATE (R) Plating |
| Body           | Brass      | SUCOPLATE (R) Plating |
| Insulator      | PFA / PTFE |                       |
| Crimp ferrule  | Copper     | SUCOPLATE (R) Plating |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00007956   |
| Catalogue drawing    | DOU-00005829   |
| Assembly instruction | DOC-0000183265 |

### Ordering Information

|                      |                      |
|----------------------|----------------------|
| Single package       | 11_QMA-50-2-1/133_NE |
| Bulk 100 pcs package | 11_QMA-50-2-1/133_NH |

### Additional Information

|                 |  |
|-----------------|--|
| Suitable cables | K_02252_D, ENVIROFLEX_316_D, G_02232_D |
|-----------------|--|

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[11\\_QMA-50-2-1/133\\_NE](#)