

HDB36-24-16 P/SN

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
N/C	NEW RELEASE PER E.O. 91285	6-8-81	TH

KEY, MAIN POLARIZING

INDICATOR, POLARIZING

1.530 MAX.

.085 MAX.

1.942φ MAX. OVER KNURL

1.477φ MAX.

.910 ±.015

PINS

SOCKETS

CABLE END VIEW OF CONNECTOR WITH INSERTS

3. THIS CONNECTOR SERIES WILL ACCOMMODATE THE FOLLOWING DIAMETERS.

CONTACT SIZE	MIN. O.D.	MAX. O.D.	WIRE GAGE RANGE
12	.134	.170	12 & 14

2. CONSULT FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATION.

1. PERTINENT INFORMATION: POWER CONTACTS
PIN 0460-204-12141 SOC. 0462-203-12141.

NOTE:

SIGNATURE & DATE

DR *[Signature]* 6-2-81

CHK *[Signature]* 6-8-81

PE *[Signature]* 6-4-81

APPD

SCALE NONE WT

PLUG, CONNECTOR
BREAKAWAY
BAYONET COUPLING
REAR INSERTION & REMOVAL
ENVIRONMENTAL

ENVELOPE

CP

MATL CODE

The Deutsch Company

ELECTRONIC COMPONENTS DIVISION

Manufactured in
Banning, California

B

DWG SIZE

HDB36-24-16 P/SN

CODE 11139

SHEET 1 OF 1