







Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de c FCI. Droits de reproduction FCI.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



PERFORMANCE CHARACTERISTICS

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)
RATED VOLTAGE : 500 V AC (CONT /CONT)
OPERATING TEMPERATURE : -55°C TO 125°C
CONTACT RESISTANCE 20 MΩ MAX
INSERTION FORCE : 0.75N MAX/CONT
EXTRACTION FORCE : 0.15N MIN/CONT
INSULATION RESISTANCE : 10⁴ MΩ MIN

NOTES 1. HM2R03PA5101 LEAD FREE INDICATOR : LF=LEAD FREE(DIGIT 15&16)
PLATING CODE(DIGIT 13&14)

Plating code	Plating	Performance Level
AA	0.75μm Au	IEC performance level 2(250mating cycles)orTELCORDIA CO
AB	1.25μm Au	TELCORDIA UE

- THIS PRODUCT IS CSA APPROVED.
THIS PRODUCT IS UL RECOGNIZED.
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :
BSA.201572.001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND
OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	DG09-0243	NZ	2009.12.1
B	DG10-0093	NZ	2010.3.8
C	DG10-0110	NZ	2010.6.8

Material			Spec ref				
Mat code			✓	tolerance	projection	MM	
Heattreat				1DEC ± 0.2 1DEC 2DEC ± 0.1 2DEC ANGLES ± 1° HOEKEN			
Plating/Finish							
Dr	Nickor Zuo	Jul-20-09				size A4	Scale 2.000
Eng	Nickor Zuo	Jul-20-09	Product family MILLIPACS				
Chr	PeiMing Zheng	Jul-20-09	Model Name		ECN		
Appr	Joseph Hsia	Jul-20-09	Model Revision		REL Level		
FCI		title	MPACS 5+2R RA RCP CONN TYPE C			dwg no BSC201418062	Rev. C
Pro/E file	catalog no	HM2R03PA5101----		CUSTOMER DRAWING		sheet 1 of 1	