


Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.





All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51761- A00CCDDEF..
NOTE ①
SEE NOTE 1



SEE NOTE 9



mat'l code SEE NOTE 2				tolerances unless otherwise specified			CUSTOMER COPY		FCI www.fciconnect.com		
lrr	ecn no.	dr	date	linear	.XX±.01/.X±.3			projection 	title RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL/ POWER		
K	DG07-0059	RYAN	02/12/07		.XXX±.005/.XX±.13						
L	DG07-0061	JULIA	02/14/07		.XXXX±.0020/.XXX±.051						
M	DG08-0239	JC	09/11/08	angles	0°±2°			INCH / MM 	product family PWRBLADE		
N	DG09-0128	JW	04/23/09	dr	D80GLE 05-18-99						
P	DG11-0074	HZ	03/14/11	enr	J. BROWN 05-18-99						
				chr	J. BROWN 05-18-99			scale 1:1	size dwg no A 51761		code 213 SHEET 1 OF 3
				appd	J. BROWN 05-18-99						
sheet index	revision sheet	P 1	P 2	P 3							
3									cage code 22526		4

form no. 7530-001-103

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51761-A00CCCDDEF-- NOTE ①
SEE NOTE 1

1	2									3	4
DIM		LENGTH FORMULAS (SEE NOTE 10)									
DIM "A"		.250 [6.35] x DD + .100 [2.54] x (CCC/4) + .650 [16.51] (NOTE 10)									
DIM "B"		.250 [6.35] x DD + .100 [2.54] x (CCC/4) + .350 [8.89]									
DIM "C"		.250 [6.35] x DD + .100 [2.54] x (CCC/4) + .300 [7.62]									
DIM "D"		.250 [6.35] x DD + .375 [9.53] $\triangle$ P									
DIM "F"		.250 [6.35] x DD + .100 [2.54] x (CCC/4) + .680 [17.27]									
DIM "G"		.250 [6.35] x DD + .225 [5.72]									

CONNECTOR NOTES

- ① PRODUCT NUMBER CODE:
51761 - A 00 CCC DD E F LF
- NO THIS SUFFIX: 100u"/2.54um SnPb ON PCB INTERFACE
ADD THIS SUFFIX: 78u"/2.00um Sn ON PCB INTERFACE
RETENTION TO PCB (NOTE 8)
TAIL OPTIONS (NOTE 7)
NUMBER OF LEFT END POWER CONTACTS (NOTE 6)
NUMBER OF SIGNAL CONTACTS (NOTE 5)
ALWAYS '00' (ZERO, ZERO) (NOTE 4)
PLATING (NOTE 3)
BASE NUMBER

- ② HOUSING MATERIAL: GLASS FILLED V-O HIGH TEMP THERMO PLASTIC.
SIGNAL CONTACT MATERIAL: COPPER ALLOY
POWER CONTACT MATERIAL: COPPER ALLOY
- ③ PLATING OPTION:
SEE PRINT 10064183 FOR PLATING SPEC OF 51761-100CCCDDEF; 51761-100CCCDDEFLF
- ④ THIS PART IS NOT AVAILABLE WITH RIGHT SIDE POWER CONTACTS.
- ⑤ SIGNAL CONTACTS, 004 TO 148 AVAILABLE FOR SOLDER TO BOARD.
012 TO 148 AVAILABLE FOR PRESS FIT TO BOARD.
- ⑥ LEFT END POWER CONTACTS, 01 TO 20 AVAILABLE.
MAXIMUM OF 20 POWER CONTACTS PER CONNECTOR
- ⑦ TAIL OPTIONS:
A = .135 ±.010 [3.43 ±0.25] SOLDER TO BOARD
B = .090 ±.005 / -.010 [2.29 ±0.13 / -0.25] SOLDER TO BOARD
C = .154 ±.010 [3.91 ±0.25] PRESS FIT TO BOARD

- ⑧ RETENTION TO PCB OPTIONS:
A = BOARD LOCK (REQUIRES .098 ±.002/-0.001 [2.49 ±0.05/-0.03] THRU HOLE IN PCB
MOUNTING FOOT HEIGHT: .220 [5.59]
B = .150 [3.81] THRU HOLE (REQUIRES .158 ±0.003 [4.01 ±0.08] THRU HOLE IN PCB).
MOUNTING FOOT HEIGHT: .160 [4.06]
- ⑨ MANUFACTURE'S NAME, P/N, AND DATE CODE TO APPEAR ON THIS SURFACE.
10. THE MAXIMUM OVERALL LENGTH (DIM A) OF A PART IS 8.00 [203.2]
11. PRODUCT SPECIFICATION GS-12-149
12. APPLICATION SPECIFICATION BUS-20-067.
13. FOR PRESS FIT CONNECTORS USE FCI CAM TOOL 430140-XXX TO APPLY CONNECTOR TO IPCB.

PCB NOTES:

14. ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE SPECIFIED.
15. ALL THROUGH HOLES ARE LOCATED WITH A TRUE POSITION OF .004 [0.10]
16. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZE.
17. $\varnothing$ 0.0453 +/- .001 [1.151 ±0.02] DRILLED HOLES PLATED WITH 0.0003 [0.007] MIN SnPb OR Sn OVER 0.001 [0.03] TO .003 [0.08] Cu PLATING TO ACHIEVE A .040 ±.003 [1.02 ±0.08] HOLE.
18. A $\triangle$ P SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

THIS FILE WAS ORIGINALLY CREATED IN THE PRO ENGINEER ENVIRONMENT AND ANY FUTURE REVISIONS TO THIS FILE MUST BE MADE IN THE PRO ENGINEER ENVIRONMENT

mat'l code				tolerances unless otherwise specified		CUSTOMER COPY				www.fciconnect.com	
lfr	ecn no.	dr	date	linear	.XX±.01/.XX±.3	projection 	title RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL / POWER				
P					.XXX±.005/.XX±.13						
					.XXX±.0020/.XX±.051						
				angles	0°±2°	INCH / MM  scale 1:1	product family size A	PWRBLADE		code	
				dr	D.BOGLE 05-18-99			size dwg no 51761	SHEET 2 OF 3		
				enrg	J. BROWN 05-18-99						
				chr	J. BROWN 05-18-99						
				apdd	J. BROWN 05-18-99						
sheet index		revision sheet									

form no. 7530-001-103

1 2

3

cage code 22526





4

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de FCI. Droits de reproduction FCI.



All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.

PRODUCT NUMBER
51761 - A00CCCDDEF--
NOTE ①



mat'l code				tolerances unless otherwise specified				CUSTOMER COPY		 www.fciconnect.com			
lfr	ecr no.	dr	date	linear	.XX±.01/.X±.3		projection 	title RIGHT ANGLE RECEPTACLE w/GUIDE PIN SIGNAL / POWER	product family PWRBLADE	code 213	sheet index	revision sheet	
P					.XXX±.005/.XX±.13								
				angles	.XXX±.0020/.XXX±.051				size A	dwg no 51761			
					0°±2°								
				dr	J. BROWN	05-18-99	INCH / MM scale 1:1						
				enr	J. BROWN	05-18-99							
				chr	J. BROWN	05-18-99							
				appd	J. BROWN	05-18-99							
					</								

form no. 7530-001-103

cage code 22526