

**D-USB Connectors**



**Specification**

> <u>Standard</u> <b>(SDB)</b> D-SUB	> <u>High Density</u> <b>(HDB)</b> High Density D-SUB
---	--

**Number of Contacts**

09, 15,, 25, 26...78 Contacts  
Ex. 09 Pin = **(09)**

**Connector Body (Style)**

> <u>For Receptacle</u> <b>(P)</b> Front Fastened	> <u>For Overmolded with Cable</u> <b>(A)</b> With Strain Relief > <u>For Field installable</u> <b>(B)</b> Without Strain Relief
--	---

**Connector (Housing) Gender**

<b>(M)</b> Male Connector	<b>(F)</b> Female Connector
---------------------------	-----------------------------

**Contact Gender**

<b>(M)</b> Male (Plug)	<b>(F)</b> Female (Jack)
------------------------	--------------------------

**Assemble Style**

> <u>For Receptacle</u> <b>(S)</b> Solder Type <b>(P)</b> PCB Type (90° / 180°)	> <u>For Overmolded with Cable</u> <b>(M)</b> Overmolded with Cable > <u>For Field Installable</u> <b>(A)</b> Field Installable (Solder) <b>(C)</b> Field Installable (Crimped)
---	---

**Mating Style**

<b>(S)</b> Screw Thread	<b>(Q)</b> Automated Latch
-------------------------	----------------------------

**Backshell**

> <u>For Receptacle</u> (With Board Lock) <b>(A)</b> Straight <b>(B)</b> Right Angle (Without Board Lock) <b>(L)</b> Straight <b>(R)</b> Right Angle	> <u>For Overmolded with Cable</u> (Without Board Lock) <b>(L)</b> Straight > <u>For Field Installable</u> (Without Board Lock) <b>(L)</b> Straight
--	--

**Waterproof Rating**

**(7)** IP 67  
**(8)** IP 68

**More Information**

> <u>For Receptacle</u> (001), (002)..... Without Cable : Different Versions	> <u>For Overmolded with Cable</u> <b>(□)</b> + <b>(■)</b> : Cable Type + Cable Length EX. <b>(A01)</b> = UL2464 Cable + 1M  <b>(□)</b> : Cable Type <b>(■)</b> : Cable Length <b>(A)</b> UL2464 Cable      From 1M to 99M EX. <b>(01)</b> = 1M
--	---