



Quality Products. Service Excellence.

Hard Wired 168 Series



Features

- Single winding, does not provide isolation, for use where equipment is already isolated and only voltage change is required.
- Flexible world wide applications, 50 or 60 Hz. operation, 115VAC input.
- Output taps @ 85, 95, 105, 110, 115 and 125VAC.
- Ideal for manual line voltage adjustment for electronic equipment or small appliance operation.
- Models 168B, 168C & 168D are CSA certified (209651)
- Connection by flexible leads, 8" minimum length.
- Remember - These units do NOT convert line frequency



| Part No. | Capacity | Overall Dimensions | | | | | Weight |
|----------|----------|--------------------|------|------|------|------|--------|
| | VA | A | B | C | D | E | Lbs |
| 168B | 200 | 3.13 | 3.30 | 3.80 | 2.50 | 1.90 | 4.3 |
| 168C | 350 | 3.13 | 4.00 | 3.80 | 2.50 | 2.70 | 6.5 |
| 168D | 500 | 3.75 | 4.00 | 4.60 | 3.00 | 2.80 | 8 |
| 168E | 750 | 3.75 | 4.50 | 4.60 | 3.00 | 3.30 | 10 |
| 168F | 1000 | 3.75 | 5.50 | 4.60 | 3.00 | 4.30 | 14 |
| 168H | 1500 | 4.38 | 6.10 | 5.30 | 3.50 | 4.50 | 20 |
| 168J | 2000 | 4.38 | 6.60 | 5.30 | 3.50 | 5.10 | 23 |

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.