

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0765001817

Status:

Active

Overview:


Impact™ Backplane Connector and Cable Assembly System

Description:

Impact™ 100 Ohm 4 Pair RAM Right Angle Header, Unguided, Left Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free

|                                                              |                                                               |
|--------------------------------------------------------------|---------------------------------------------------------------|
| Documents:                                                   |                                                               |
| <a href="#">3D Model</a>                                     | <a href="#">Application Specification AS-76060-994 (PDF)</a>  |
| <a href="#">Drawing (PDF)</a>                                | <a href="#">Application Specification AS-76060-9999 (PDF)</a> |
| <a href="#">Product Specification PS-76060-999 (PDF)</a>     | <a href="#">Packaging Specification PK-70873-041 (PDF)</a>    |
| <a href="#">Application Specification AS-76060-990 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>          |

|                                |                                                       |
|--------------------------------|-------------------------------------------------------|
| Agency Certification           |                                                       |
| UL                             | E29179                                                |
| General                        |                                                       |
| Product Family                 | Backplane Connectors                                  |
| Series                         | 76500                                                 |
| Application                    | Coplanar                                              |
| Application Tooling Documents  | TM-622018799                                          |
| Component Type                 | PCB Header                                            |
| Overview                       | Impact™ Backplane Connector and Cable Assembly System |
| Product Name                   | Impact™                                               |
| UPC                            | 884982022577                                          |
| Physical                       |                                                       |
| Circuits (Loaded)              | 96                                                    |
| Circuits (maximum)             | 96                                                    |
| Color - Resin                  | Black                                                 |
| Durability (mating cycles max) | 200                                                   |
| First Mate / Last Break        | No                                                    |
| Flammability                   | 94V-0                                                 |
| Guide to Mating Part           | No                                                    |
| Keying to Mating Part          | None                                                  |
| Material - Metal               | High Performance Alloy (HPA)                          |
| Material - Plating Mating      | Gold                                                  |
| Material - Plating Termination | Tin                                                   |
| Material - Resin               | High Temperature Thermoplastic                        |
| Net Weight                     | 9.290/g                                               |
| Number of Columns              | 8                                                     |
| Number of Pairs                | 4                                                     |
| Number of Rows                 | 12                                                    |
| Orientation                    | Right Angle                                           |
| PC Tail Length                 | 1.20mm                                                |
| PCB Locator                    | No                                                    |
| PCB Retention                  | Yes                                                   |
| PCB Thickness - Recommended    | 1.00mm                                                |
| Packaging Type                 | Tray                                                  |
| Pitch - Mating Interface       | 1.90mm                                                |
| Pitch - Termination Interface  | 1.90mm                                                |
| Plating min - Mating           | 0.762µm                                               |
| Polarized to PCB               | No                                                    |
| Stackable                      | No                                                    |
| Temperature Range - Operating  | -55°C to +85°C                                        |
| Termination Interface: Style   | Through Hole - Compliant Pin                          |



Series image - Reference only

|                                                                                               |              |
|-----------------------------------------------------------------------------------------------|--------------|
| EU ELV                                                                                        |              |
| Not Relevant                                                                                  |              |
| EU RoHS                                                                                       | China RoHS   |
| Compliant                                                                                     |              |
| REACH SVHC                                                                                    |              |
| Not Contained Per                                                                             |              |
| -ED/79/2015 (17                                                                               |              |
| December 2015)                                                                                |              |
| Halogen-Free                                                                                  |              |
| Status                                                                                        |              |
| Low-Halogen                                                                                   |              |
| Need more information on product environmental compliance?                                    |              |
| Email <a href="mailto:productcompliance@molex.com">productcompliance@molex.com</a>            |              |
| Please visit the <a href="#">Contact Us</a> section for any non-product compliance questions. |              |
| China ROHS                                                                                    | Green Image  |
| ELV                                                                                           | Not Relevant |

Search Parts in this Series

76500 Series

Mates With

76160 Impact™ 100 Ohm Daughtercard

|                                                                                                                                                                                 |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Application Tooling   FAQ                                                                                                                                                       |            |
| Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. |            |
| Global                                                                                                                                                                          |            |
| Description                                                                                                                                                                     | Product #  |
| Press-In Tool for Daughter Card Module                                                                                                                                          | 0622018677 |
| Impact™ Right Angle Module Removal Tool (RAM)                                                                                                                                   | 0622024350 |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Data Rate                     | 25.0 Gbps       |
| Impedance                     | 100#            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Solder Process Data**

|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

**Material Info**

**Reference - Drawing Numbers**

|                           |                                           |
|---------------------------|-------------------------------------------|
| Application Specification | AS-76060-990, AS-76060-994, AS-76060-9999 |
| Electrical Model Document | EE-76500-002                              |
| Packaging Specification   | PK-70873-041                              |
| Product Specification     | PS-76060-999                              |
| S-Parameter Model         | SP-76500-002                              |
| Sales Drawing             | SD-76500-001                              |
| Symbol/Footprint Data     | SYM-76500-1817                            |

This document was generated on 06/09/2016

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**