

Coaxial Cable Connector 25_NEX10-50-3-1/033_-

Description

Straight panel cable jack, flange mount

Interface standards

NEX10



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	20 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered

Environmental Data

Operating temperature	-55 °C to 125 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Silver Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Related Documents

Outline drawing	DOU-00327075
Catalogue drawing	DCA-00343824
Assembly instruction	DOC-0000764177

Ordering Information

Bulk 100 pcs package	25_NEX10-50-3-1/033_-H
----------------------	------------------------

Additional Information

Suitable cables	SUCOFORM_141_CU_FEP
-----------------	---------------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[25_NEX10-50-3-1/033_-H](#)