

PCB terminal block - FFKDSA1/H-2,54- 5 MIXCYE/GY - 1712231

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB terminal block, nominal current: 6 A, nom. voltage: 160 V, pitch: 2.54 mm, number of positions: 5, connection method: Push-in spring connection, mounting: Wave soldering, color: multi-color. The article can be aligned to create different nos. of positions!

The figure shows a 1-pos. version of the product

Your advantages

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Operation and conductor connection from one direction enable integration into front of device
- ✓ Two solder pins reduce the mechanical strain on the soldering spots
- ✓ The latching on the side enables various numbers of positions to be combined



Key Commercial Data

Packing unit	50 pc
GTIN	
GTIN	4055626287508

Technical data

Dimensions

Length [l]	13.6 mm
Pitch	2.54 mm
Dimension a	10.16 mm
Width [w]	10.16 mm
Height	12.6 mm
Height [h]	16.2 mm
Solder pin [P]	3.6 mm
Hole diameter	1.1 mm

General

PCB terminal block - FFKDSA1/H-2,54- 5 MIXCYE/GY - 1712231

Technical data

General

Range of articles	FFKDS(A) 0,5/...H
Insulating material group	I
Rated voltage (III/2)	160 V
Nominal current I _N	6 A
Nominal cross section	0.5 mm ²
Flammability rating according to UL 94	V0
Number of positions	5

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>