



### Main

|                              |                                                           |
|------------------------------|-----------------------------------------------------------|
| Device short name            | C                                                         |
| Enclosure type               | Dust and damp proof weatherproof enclosure indoor/outdoor |
| Product specific application | Condensation pump                                         |
| Switch application           | Standard                                                  |

### Complementary

|                       |                                                                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical connection | Screw clamp terminal                                                                                                                                                |
| Float movement        | 4...7.75 in                                                                                                                                                         |
| Float position        | Left                                                                                                                                                                |
| Material              | Stainless steel float/rod<br>Nitrile (Buna-N) seal ring                                                                                                             |
| Motor power hp        | 1 hp at 460/575 V AC for 3 phases<br>2 hp at 115 V AC for 1 phase<br>3 hp at 115 V AC for 3 phases<br>3 hp at 230 V AC for 1 phase<br>5 hp at 230 V AC for 3 phases |
| Mounting support      | Flange                                                                                                                                                              |
| Number of poles       | 2                                                                                                                                                                   |
| Permissible voltage   | <= 575 V AC                                                                                                                                                         |
| Switch function       | DPST                                                                                                                                                                |

### Environment

|                           |        |
|---------------------------|--------|
| NEMA degree of protection | NEMA 4 |
|---------------------------|--------|

### Offer Sustainability

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                        | Not Green Premium product                                                                                                        |
| Will not be Compliant                                                                                                            | Will not be Compliant                                                                                                            |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| Di-isodecyl phthalate (DIDP) which is known to the State of California to cause birth defects or other reproductive harm.        | Di-isodecyl phthalate (DIDP) which is known to the State of California to cause birth defects or other reproductive harm.        |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.