



Part No: CLS0301MA-L152

Date: 7/03/2007

Unit: mm

Description: speaker


Page No: 1 of 2

Specifications




Nominal Size	30 mm		
Impedance	8 Ohm ± 15%	at	1 KHz 1 V
Resonant frequency	550 Hz ± 110 Hz	at	1 V
Sound pressure level	89 dB/w ± 3 dB 1 w 50 cm ave. at 0.8K, 1K, 1.2K, 1.5K Hz		
Response	Fo Hz ~ 13 KHz max 10 dB		
Input power	Nominal 0.2 W	Handling capacity	0.4 W
Operation	must be normal at program source 0.2 W		
Buzz, rattle, etc.	must be normal at sine wave 1.26 V		
Magnet	Size: 12.5 x 1.0 mm		
Load test	White noise	0.2 W for	24 hours
Heat test	70 ± 2° C	20-50% R.H.	24 hours
Humidity test	40 ± 2° C	90-95% R.H.	24 hours

Frequency Response Curve

Potentiometer range	50 dB
Rectifier	RMS
Lower limit frequency	20 Hz
Wr. speed	100 mm/sec

Zero level 60 dB

REV.	DESCRIPTION	DATE
A	NEW DRAWING	7/3/2007



SPECIFICATIONS:
WIRE: UL1007, #28AWG
LENGTH: 152mm

TOLERANCE:
 $\pm$ 0.5mm UNLESS OTHERWISE
SPECIFIED



CUI INC

20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-612-2383
Website: www.cui.com

TITLE: LOW PROFILE SPEAKER		REV: A
PART NO. CLS0301MA-L152	UNITS: MM [INCHES]	
DRAWN BY: ZRJ	APPROVED BY:	SCALE: 2:1