

Page
1 / 2

OPTIONS : / TTL DRIVE /SUPP.DIODES

NUMBER OF WAYS : 6
FREQUENCY RANGE : 0 - 3 GHz
IMPEDANCE : 50 Ohms

FREQUENCY (GHz)	0 - 3
V.S.W.R	<= 1.20
INSERT. LOSS	<= 0.20 dB
ISOLATION	>= 80 dB
AVER. POWER (*)	240 W

ACTUATOR	: NORMALLY OPEN
NOMINAL CURRENT AT 25° C (±10%)	: 250 mA
ACTUATOR VOLTAGE (Vcc)	: 12V (10.2 to 13V) / NEGATIVE COMMON
TERMINALS	: solder pins (250°C max./30 sec.)
TTL INPUTS (E) - High level	: 2.2 to 5.5V / 800µA at 5V
- Low level	: 0 to 0.8V / 20µA at 0.8V

CONNECTORS	: SMA female	per MIL C 39012
LIFE	: 5.000.000	cycles per position
SWITCHING TIME (nominal voltage;25° C)	: < 15	ms
CONSTRUCTION	: splashproof	
WEIGHT	: < 220	g

OPERATING TEMPERATURE RANGE (°C) : -40 , +85
STORAGE TEMPERATURE RANGE (°C) : -55 , +85

(* : average power at 25° C per RF path)


This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary

DRAWING


General tolerance: ± 0,5 mm

R573 302 620

Page
2/2




TTL input	RF continuity
E1 = 1	IN ↔ 1
E2 = 1	IN ↔ 2
E3 = 1	IN ↔ 3
E4 = 1	IN ↔ 4
E5 = 1	IN ↔ 5
E6 = 1	IN ↔ 6




MARKING

TOP VIEW (TERMINALS)



SCHEMATIC DIAGRAM



ISSUE 22.Jan.08

4113-9212