


D


C

B

A




NOTCH DESIGNATES ROW A





LOC		DIST		REVISIONS				
AD	00	P	LYR	DESCRIPTION	DATE	OWN	APVD	
		1		DRAWING CREATED BY AUTOMATION PROGRAM	05JAN2011	-	JE	
		A		RELEASED	28FEB2012	BC	DY	

- 1 MATERIAL:
HOUSING: LCP, GLASS FILLED, UL94V-0.
TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
- 2 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN
ON PCB TAILS, NICKEL OVERALL.
- 3 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN-LEAD
ON PCB TAILS, NICKEL OVERALL.
4. SCREWS PACKAGED IN END OF PACKAGING TUBE.
- 5 FOR GROUNDED GUIDE PIN USE Ø3.56±0.08 PTH,
Ø3.66 DRILL, AND Ø6.5 PAD.
6. KEYING PIN SHOWN IN POSITION A. SEE KEYING CHART
ON SHEET 2 FOR OTHER POSITIONS.



RIGHT GUIDED
BACKPLANE HOLE PATTERN
(CONNECTOR SIDE)



THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN	05JAN2011	TE Connectivity	
DIMENSIONS:		CHK	J. EABY		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	J. EABY	NAME	
mm		05JAN2011		IMPACT, 3 PAIR, 6 COLUMN, HEADER	
9 PLC ±		PRODUCT SPEC		RIGHT GUIDED, OPEN END WALL	
1 PLC ±0.25		APPLICATION SPEC		SIGNAL MODULE, 0.39 PTH	
2 PLC ±0.13		SIZE		RESTRICTED TO	
3 PLC ±		WEIGHT		A100779C=2132531	
4 PLC ±		CUSTOMER DRAWING		SCALE 6:1 SHEET 1 OF 2 REV A	
ANGLES ±					
FINISH SEE TABLE					

LOC		DIST		REVISIONS						
AD		00		P	LTR	DESCRIPTION		DATE	DWN	APVD
				-	-	SEE SHEET 1		-	-	-

	H	5.5	8-2132531-6
	H	4.9	8-2132531-5
	H	4.5	8-2132531-4
	H	5.5	8-2132531-3
	H	4.9	8-2132531-2
	H	4.5	8-2132531-1
	G	5.5	7-2132531-6
	G	4.9	7-2132531-5
	G	4.5	7-2132531-4
	G	5.5	7-2132531-3
	G	4.9	7-2132531-2
	G	4.5	7-2132531-1
	F	5.5	6-2132531-6
	F	4.9	6-2132531-5
	F	4.5	6-2132531-4
	F	5.5	6-2132531-3
	F	4.9	6-2132531-2
	F	4.5	6-2132531-1
	E	5.5	5-2132531-6
	E	4.9	5-2132531-5
	E	4.5	5-2132531-4
	E	5.5	5-2132531-3
	E	4.9	5-2132531-2
	E	4.5	5-2132531-1
	D	5.5	4-2132531-6
	D	4.9	4-2132531-5
	D	4.5	4-2132531-4
	D	5.5	4-2132531-3
	D	4.9	4-2132531-2
	D	4.5	4-2132531-1
	C	5.5	3-2132531-6
	C	4.9	3-2132531-5
	C	4.5	3-2132531-4
	C	5.5	3-2132531-3
	C	4.9	3-2132531-2
	C	4.5	3-2132531-1
	B	5.5	2-2132531-6
	B	4.9	2-2132531-5
	B	4.5	2-2132531-4
	B	5.5	2-2132531-3
	B	4.9	2-2132531-2
	B	4.5	2-2132531-1
	A	5.5	1-2132531-6
	A	4.9	1-2132531-5
	A	4.5	1-2132531-4
	A	5.5	1-2132531-3
	A	4.9	1-2132531-2
	A	4.5	1-2132531-1
	-	5.5	2132531-6
	-	4.9	2132531-5
	-	4.5	2132531-4
	-	5.5	2132531-3
	-	4.9	2132531-2
	-	4.5	2132531-1
FINISH	KEY POSITION	DIM M	PART NUMBER

REFER TO WWW.TE.COM
FOR PRODUCT AVAILABILITY

KEY POSITION
CHART

NONE

A

E

B

F

C

G

D

H