

P-Channel Power MOSFET

-20V, -6.5A, 26mΩ

FEATURES



- Fast switching
- Suitable for -1.8V Gate Drive Applications
- Pb-free plating
- RoHS compliant
- Halogen-free mold compound

KEY PERFORMANCE PARAMETERS

PARAMETER	VALUE	UNIT
V_{DS}	-20	V
I_D	-6.5	A
$R_{DS(on)}$ (max)	$V_{GS} = -4.5V$	26
	$V_{GS} = -2.5V$	32
	$V_{GS} = -1.8V$	40
Q_g	19.5	nC

APPLICATION

- Battery Pack
- Portable Devices


Notes: Moisture sensitivity level: level 3. Per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 10	V
Continuous Drain Current	I_D	$T_C = 25^\circ\text{C}$	A
		$T_C = 100^\circ\text{C}$	
Pulsed Drain Current (Note 1)	I_{DM}	-26	A
Total Power Dissipation	P_{DTOT}	1.56	W
Operating Junction Temperature	T_J	150	$^\circ\text{C}$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	- 55 to +150	$^\circ\text{C}$

THERMAL PERFORMANCE

PARAMETER	SYMBOL	LIMIT	UNIT
Junction to Ambient Thermal Resistance	$R_{\theta JA}$	80	$^\circ\text{C/W}$

Notes: $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. $R_{\theta JA}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. $R_{\theta JA}$ is shown for single device operation on FR-4 PCB in still air.

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static ^(Note 2)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	BV _{DSS}	-20	--	--	V
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	V _{GS(TH)}	-0.3	-0.6	-1.0	V
Gate Body Leakage	V _{GS} = ±10V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V _{DS} = -20V, V _{GS} = 0V	I _{DSS}	--	--	-1	μA
	V _{DS} = -16V, T _J = 125°C		--	--	-10	
Drain-Source On-State Resistance	V _{GS} = -4.5V, I _D = -5A	R _{DS(on)}	--	21	26	mΩ
	V _{GS} = -2.5V, I _D = -4A		--	26	32	
	V _{GS} = -1.8V, I _D = -3A		--	32	40	
Forward Transconductance	V _{DS} = -10V, I _S = -5A	g _{fs}	--	15	--	S
Dynamic ^(Note 3)						
Total Gate Charge	V _{DS} = -10V, I _D = -5A, V _{GS} =- 4.5V	Q _g	--	19.5	--	nC
Gate-Source Charge		Q _{gs}	--	2	--	
Gate-Drain Charge		Q _{gd}	--	3.6	--	
Input Capacitance	V _{DS} = -15V, V _{GS} = 0V, F = 1.0MHz	C _{iss}	--	1670	--	pF
Output Capacitance		C _{oss}	--	220	--	
Reverse Transfer Capacitance		C _{rss}	--	120	--	
Switching						
Turn-On Delay Time	V _{DD} = -10V, I _D = -1A, V _{GS} = -4.5V, R _{GEN} =25Ω	t _{d(on)}	--	10.4	--	ns
Turn-On Rise Time		t _r	--	37.5	--	
Turn-Off Delay Time		t _{d(off)}	--	89.1	--	
Turn-Off Fall Time		t _f	--	24.6	--	
Source-Drain Diode						
Forward Voltage	V _{GS} = 0V, I _S = -1A	V _{SD}	--	--	-1	V
Continuous Forward Current	Integral reverse diode in the MOSFET	I _S	--	--	-6.5	A
Pulse Forward Current		I _{SM}	--	--	-26	A

Notes:

- Pulse width limited by safe operating area
- Pulse test: $PW \leq 300\mu s$, duty cycle $\leq 2\%$
- Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSM260P02CX RFG	SOT-23	3,000pcs / 7" Reel
TSM260P02CX6 RFG	SOT-26	3,000pcs / 7" Reel


Note:

1. Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
2. Halogen-free according to IEC 61249-2-21 definition


CHARACTERISTICS CURVES

($T_C = 25^\circ\text{C}$ unless otherwise noted)


Continuous Drain Current vs. T_C




Gate Charge




On-Resistance vs. Junction Temperature




Threshold Voltage vs. Junction Temperature



Maximum Safe Operating Area




Normalized Thermal Transient Impedance Curve




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)


SOT-23



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



26 = Device Code

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr


S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec


L = Lot Code

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)


SOT-26



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



26 = Device Code

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec

L = Lot Code (1~9, A~Z)

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.