



TAPE AND REEL SPECIFICATIONS:

FEED DIRECTION

## 1 TAPE:

REEL DIA. REF.

> .500 [12.7] DIA. HOLE THRU

±.005 [±0.13]

**WIDTH** 

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER ANSI/EIA-481 STANDARD

FEED DIRECTION

±.005 [±0.13]

0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

- PITCH

 $\pm .005 [\pm 0.13]$ 

±.005 [±0.13]

.457 [11.60] —

.059 [1.5] DIA.

HOLE (TYP.)

.157 [4.0]

.945 [24.0] WIDE; .473 [12.00] PITCH

**DESCRIPTION** 

## 2. REEL:

DATE

13.0 [330.2] DIA. 1500 PIECES OF PART NO. 3030 PER REEL.

	KEYSTONE ELECTRONICS CORP.  www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900  PART NAME  SM RETAINER ON TAPE  MATERIAL  AS NOTED			
	AS NOTED		DRN BY NT APP'D LN	DATE 12.30.10  SCALE X
REV.	TOLERANCES INCH [MM] DECIMAL ± .015 [± 0.38 ] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED	CODE	DWG NO. 303	BOTR