

8365	8996	9064	9280
<p>8365-0-15-XX-13-XX-10-0 Hex-pressfit in 2,69 plated thru hole.</p>	<p>8996-0-31-XX-13-XX-04-0 Compliant press-fit in 1,02±0,08 plated hole. For 1,52→2,54 thick board.</p>	<p>9064-0-15-XX-13-XX-10-0 Solder mount in 2,59 min. mounting hole Also available on 16mm wide carrier tape: 1,300 parts per 330mm reel. Order as: 9064-0-57-XX-13-XX-10-0</p>	<p>9280-0-15-XX-13-XX-10-0 Solder mount in 2,59 min. mounting hole.</p>

4900

<p>4900-0-19-XX-23-XX-10-0 Swage mount in 1,70 hole</p>			
---	--	--	--

--	--	--	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µmTIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p>SPECIFY CONTACT FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p style="text-align: center;">SELECT CONTACT #13 or #23 CONTACT (DATA ON PAGE 226)</p> <div style="text-align: center;"> </div>
--	--