

Cable - CABLE-D62SUBH/B/B/2000/K4G/GK2 - 2311917


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled, shielded round cable, with 62-pos. HD D-SUB female connector at both ends; cable length: 20 m



RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 332736
GTIN	4046356332736

Technical data

General

Nominal voltage U_N	25 V AC
	50 V DC
Max. current carrying capacity per path	1 A
Length of cable	20 m
Single wire, cross section	0.14 mm ²
Single wire, cross section [AWG]	26
External diameter	12.2 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Outer sheath, material	PVC
External sheath, color	gray

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-30 °C ... 70 °C

Connector 1

Connection name	Field level
Connection method	High-density D-SUB socket strip

Cable - CABLE-D62SUBH/B/B/2000/K4G/GK2 - 2311917

Technical data

Connector 1

Number of connections	1
Number of positions	62

Connector 2

Connection name	Controller level
Connection method	High-density D-SUB socket strip
Number of connections	1
Number of positions	62

Supported controller

Controller	Teleperm XP
------------	-------------

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>