



REV.	ECN NO.	DATE	SIGN	DESCRIPTION



ALTW
CONFIDENTIAL
2007.11.29
R&D DEPT.

ALTW
DCC. DEPT.
CONFIDENTIAL
2008.01.31
ISSUED



8	Gray	8
7	Purple	7
6	Blue	6
5	Green	5
4	Yellow	4
3	Orange	3
2	Red	2
1	Brown	1
Conn.1	Wire Color	Conn.2

Note:
* ϕ Important Dimension.
* Waterproof Rate: IP68
* Housing: Black, PU
* Male & Female Pin: Copper Alloy, Gold Plated
* Wire Harness: UL1007 24AWG, 8Pcs.
* Cable: UL2464 22AWG*8C+Talc
Black, PVC Jacket UV Resistant OD=5.5mm
* Cable Length Tolerance: 1M~10M $\pm$ 5%mm, 11M~99 $\pm$ 500mm.

UNIT:mm		TITLE	M12 Conn T Cable Screw	ITEM NO	DRAWN BY	DATE
TOLERANCE		SCALE	MF Conn MF Pin	DWG NO	CHECKED BY	DATE
± 0.5 mm		REV.	A	SIZE	APPROVED BY	DATE
1	2	3	4	5	6	7
Amphenol LTW				DATE		
安費諾亮泰企業股份有限公司				DATE		
REV. A				DATE		
SIZE A4				DATE		
Inspection Item				DATE		
1				DATE		
2				DATE		
3				DATE		
4				DATE		
5				DATE		
6				DATE		
7				DATE		
8				DATE		