

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED AS PER ECR-15-005925	21APR2015	RS	JL
	A1	REVISED AS PER ECR-15-011749	10AUG2015	RS	JL

1.0

"PE" CONTACT

2.8
4X

PART NO.
2213234-1

M1.5 HEX
DRIVE

"PE" CONTACT

"PE" SYMBOL

1.0

"PE" CONTACT

5.2
4X

PART NO.
1-2213234-1

M1.5 HEX
DRIVE

CONTACT
(5X)

CONTACT
POSITIONER
(1X)

NOTES:

1 MATERIALS:
CONTACTS: COPPER ALLOY, TIN PLATE
CONTACT POSITIONER: GLASS FILLED PBT,
COLOR BLACK

2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)


3. CONTACTS (5X) ARE PRE-ASSEMBLED INTO CONTACT
POSITIONER AS SHOWN.

4 CONTACTS ARE NOT INSTALLED
INTO THE INDICATED CONTACT SLOTS

5 "PE" SYMBOL ALIGNS WITH "PE"
CONTACT AS SHOWN

6. THIS PRODUCT HAS NOT COMPLETED
VALIDATION TESTING

IEC (DEKRA)	1-2213234-1
UL	2213234-1
AGENCY APPROVALS	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. SHAFFER 15JAN2014	 TE Connectivity		
DIMENSIONS: mm		CHK M. LUKSIC 15JAN2014			NAME
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. LUKSIC 15JAN2014			SCREW TERMINAL PIN CONTACTS ASSY, 5POSN, NECTOR M-LINE SEALED
0 PLC ±- 1 PLC ±0.2 2 PLC ±0.13 3 PLC ±- 4 PLC ±- ANGLES ±- FINISH -		PRODUCT SPEC 108-133014			RESTRICTED TO
MATERIAL NOTE 1		APPLICATION SPEC 114-32111	SIZE A3	CAGE CODE -	
		WEIGHT -	DRAWING NO C-2213234		
		Customer Drawing	SCALE 1:1	SHEET 1 OF 1	
				REV A1	

1470-19 (3/13)