

400-Watt High Bay Light

Temporary Lighting
Fixture For
Construction Sites



High Bay Light

Woodhead
LIGHTING

another **bright idea** from Woodhead

The New Woodhead 400-Watt High Bay Light is an economical, efficient and cost-effective temporary lighting fixture for use on commercial, industrial and residential construction sites, as well as loading docks, warehouses and staging areas.

This high-output metal halide fixture is designed to meet OSHA requirements for minimum illumination of work areas when properly installed. The Woodhead 400-Watt High Bay Light provides more light than two 100' temporary stringlights and is much easier to install.

- 400-watt, clear, metal halide lamp (included) meets OSHA 1926.56 for minimum illumination of work areas when mounted 15' above 40' x 40' and 60' x 60' bays.
- Type "O" lamp and mogul socket complies with NEC 2005 410.73(F)(5) and ANSI C78.387 to prevent the use of lamps without filament protection and increases job safety.
- Multi-tap style ballast operates on several different voltages that are available at most job sites. Open-air design allows the fixtures to cool sufficiently and operate at optimum temperatures.
- Hook with spring-loaded clamp allows faster installation compared to running two, 100' temporary lighting strings. The unit mounts quickly, easily and securely without any loose springs or the use of tools.
- Two, 3/4" knock-outs, located on both sides of the wiring compartment provide easy feed-thru connections or multi-voltage power supplies when using conduit.
- Heavy-gauge, welded and plated guard provides superior lamp protection in abusive environments. Wire-formed guard attaches to the enclosure rather than the porcelain lampholder, resisting breakage during severe impacts.

Specifications

Description	400-Watt High Bay Temporary Lighting Fixture
Voltages	120V/208V/240V/277V, 60 Hz
Light Output	36,000 Initial Lumens at 4200°K Color Rendering
Lamp Style	400-Watt MH, O-Type, BT37 clear, EX39 mogul base
Lamp Life	20,000 Approximate Standard Hours
Height	24" Overall, 13" Guard Height
Width	4" x 5" Fixture Profile, 10" Diameter Guard
Cordset	3 ft., #18-3 SJTW Cordset with NEMA 5-15 Plug
Agency Approval	UL, CUL, File #E174254

Ordering Information

Cat. No.	Description
8575-MH	400-Watt Metal Halide Temporary Lighting Fixture
34-0029	Replacement Lamps for 8575-MH



400- Watt High Bay Light



Spring-Loaded Safety Clamp



Knockouts On Both Sides
For Conduit Connections



Guard Attached To Enclosure,
Not To Lampholder



Woodhead®
LIGHTING

from Woodhead Industries

800.225.7724 • woodhead.com

©2006 Woodhead Industries DW2006126 CPI 30M