

Contactors

3 Pole / Frame Size 400AF



Altech Corp.[®]

includes 2 x AU-100-11
Auxiliary switch,
(2NO/2NC)

Additional Auxiliaries
and other accessories
see page 11-13

| Type | MC-265A | MC-330A | MC-400A |
|----------------------|---------|---------|---------|
| Number of Poles | 3 | 3 | 3 |
| NEMA Size | 5 | 5 | 5 |
| Standard Auxiliaries | 2NO/2NC | 2NO/2NC | 2NO/2NC |

| | Coil Voltage | | Part. No. | Part. No. | Part. No. |
|--------------------|-------------------|-----------|------------------|------------------|------------------|
| AC/DC | AC 50/60Hz | DC | | | |
| Common Coil | 100-240V | 100-220V | MC-265A-100/200V | MC-330A-100/200V | MC-400A-100/200V |
| | 265-347V | - | MC-265A-300V | MC-330A-300V | MC-400A-300V |
| | 380-450V | - | MC-265A-400V | MC-330A-400V | MC-400A-400V |
| | 440-575V | - | MC-265A-500V | MC-330A-500V | MC-400A-500V |

| HP Rating / UL508 | | HP | HP | HP |
|-------------------|--------------------|------|------|------|
| | Continuous current | 300A | 350A | 450A |
| Single phase | 110~120V | - | - | - |
| | 220~240V | - | - | - |
| Three phase | 200~208V | 75 | 100 | 125 |
| | 220~240V | 100 | 125 | 150 |
| | 440~480V | 200 | 250 | 300 |
| | 550~600V | 200 | 250 | 300 |

Overload Relays

(Class 10A,
Differential Typical)



MT-400

| Setting Ranges (A) | Frame Size 400AF |
|--------------------|------------------|
| 85-125A | MT-400/3K-125 |
| 100-160A | MT-400/3K-160 |
| 120-185A | MT-400/3K-185 |
| 160-240A | MT-400/3K-240 |
| 200-330A | MT-400/3K-330 |
| 260-400A | MT-400/3K-400 |

Lug Terminals



| Part. No. | Frame Size |
|-----------|------------|
| AJ-220 | 225AF |
| AJ-400 | 400AF |
| AJ-800 | 800AF |

Drawings and other technical information can be found on page 14-20.