



Heyco® Nylon Male/Female Threaded Hex Supports

ALL NEW
PRODUCTS!




4-40 x .187" MALE /
4-40 x .187" FEMALE
1/4" ACROSS FLATS

MFS4




6-32 x .250" MALE /
6-32 x .250" FEMALE
1/4" ACROSS FLATS

MFS6



8-32 x .375" MALE /
8-32 x .375" FEMALE
1/4" ACROSS FLATS

MFS8



M3 x 8,0 mm MALE /
M3 x 8,0 mm FEMALE
5,0 mm ACROSS FLATS

MFSM3

	Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter		Thread Length		Mounting Hole Diameter	
	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
Male end	.187	4,8	4-40		.250	6,4	6-32		.375	9,5	8-32		8,0	.315	M3	
Female end	.187	4,8	4-40		.250	6,4	6-32		.375	9,5	8-32		8,0	.315	M3	
A	PART NO.		DESCRIPTION		PART NO.		DESCRIPTION		PART NO.		DESCRIPTION		PART NO.		DESCRIPTION	
in. mm.	Natural				Natural				Natural				Natural			
.250 6,4	11800		MFS4-04		11820		MFS6-04 †		11840		MFS8-04 †		6,0 .236	11859		MFSM3-M06 NEW!
.276 7,0	11801		MFS4-04.4										10,0 .394	11860		MFSM3-M10
.312 7,9	11802		MFS4-05*		11822		MFS6-05*						12,0 .472	11861		MFSM3-M12
.375 9,5	11803		MFS4-06		11823		MFS6-06		11843		MFS8-06 ††		15,0 .590	11862		MFSM3-M15
.437 11,1	11804		MFS4-07		11824		MFS6-07		11844		MFS8-07		18,0 .709	11863		MFSM3-M18
.500 12,7	11805		MFS4-08		11825		MFS6-08		11845		MFS8-08		20,0 .787	11864		MFSM3-M20
.562 14,3	11806		MFS4-09		11826		MFS6-09		11846		MFS8-09		25,0 .984	11865		MFSM3-M25
.600 15,2	11807		MFS4-09.6													
.625 15,9	11808		MFS4-10		11828		MFS6-10		11848		MFS8-10					
.687 17,4					11829		MFS6-11*									
.750 19,1	11810		MFS4-12		11830		MFS6-12		11850		MFS8-12					
.875 22,2	11811		MFS4-14		11831		MFS6-14		11851		MFS8-14					
.937 23,8					11832		MFS6-15									
1.000 25,4	11813		MFS4-16		11833		MFS6-16		11853		MFS8-16					
1.125 28,6	11814		MFS4-18		11834		MFS6-18		11854		MFS8-18					
1.250 31,8	11815		MFS4-20		11835		MFS6-20		11855		MFS8-20					
1.312 33,3					11836		MFS6-21									
1.375 34,9	11817		MFS4-22		11837		MFS6-22		11857		MFS8-22					
1.500 38,1					11839		MFS6-24									
2.000 50,8	11818		MFS4-32		11838		MFS6-32		11858		MFS8-32					

Standard color natural.

† Female thread depth is .190" (4,8 mm)

†† Female thread depth is .200" (5,1 mm)

* Special order.

Quick
Specs

Material Nylon 6/6
Flammability Rating 94V-2
Temperature Range -40°F (-40°C) to 185°F (85°C)