


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION AUGUST, 2006.
 © COPYRIGHT 2006 By - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASE	13JUN2018	ED	RS

- NOTES:
- 1 PACK IN ACCORDANCE WITH TE SPEC 107-3275
 - 2 Passivation
 - 3 CuZnSn PLATING: 80u"
 - 4 Ag PLATING: 200u"
 - 5 ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED



ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Frequency Range (GHz) DC to 6GHz	Recommended coupling Torque 9-14 in-lbs(N) 177-265 in-lbs(7/16)	Temperature Rating -55°C TO +125°C
Voltage Rating (Peak) @ Sea Level 1000 V RMS	Mating cycles 500 cycles	
Insulation Resistance (MIN.) 5000 M ohms	Center contact retention force 40 lbs MIN	
Contact Resistance (Milliohms MAX) Center Contact 1.0 Outer Contact 0.4	Power handling: 300W@2GHz @90°C	
Dielectric Withstand Voltage: 2500 V RMS Max	3rd Intermodulation: <-166dBc@2X43dBm 900MHz/1800MHz	
Insertion Loss : 0.1*√F(GHz) dB		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	0 PLC ± -
	1 PLC ± 0.2
	2 PLC ± 0.1
	3 PLC ± -
	4 PLC ± -
	ANGLES ± -
MATERIAL	FINISH
SEE TABLE	-

DWN	ED	13JUN 2018
CHK	BW	13JUN 2018
APVD	RS	13JUN 2018
PRODUCT SPEC	-	
APPLICATION SPEC	-	
WEIGHT	0.000000	
CUSTOMER DRAWING		

QUANTITY PER ASSY	MATERIAL	DESCRIPTION	ITEM
1	STEEL	SHELL(N)	5
1	BRASS	SHELL(7/16)	4
1	PTFE	INSULATION	3
1	BRASS	CENTER CONTACT	2
1	BRASS	BODY	1
-1			



NAME				ADAPTER			
				N Male to 7/16 DIN Male			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO				
A3	00779	C-2081557	-				
SCALE			SHEET		REV		
2:1			1 OF 1		A		