


	I	2	3	4	5	6	7	8																																																																																																																																																																					
A	<u>REFERENCE SPECIFICATIONS</u> -NFC 93425 (in compliance with HE 507)			Series ← DBML13W3S300N					A																																																																																																																																																																				
B	<u>PHYSICAL CHARACTERISTICS</u> -INSULATOR MATERIAL: THERMOPLASTIC UL94V0 -CONTACT MATERIAL: PHOSPHOR BRONZE(SIGNAL CONTACT) GOLD OVER NICKEL -ACCESSORIES: STAINLESS STEEL or BRASS Cadmium plated, yellow passivation -SHELLS: STEEL Cadmium plated, yellow passivation			Shell size: E A B C D ← see sheet 3 M :characteristic for the DM series Front accessory definition see sheet 2 Blank :without accessory L :threaded insert M3 O :threaded insert UNC 4-40 V :female screw UNC 4-40 F :floating mounting S :spacer Layout of contacts (see sheet 3) ← Contacts ← S :Socket Termination type ← 3 Straight version Plating ← 00 straight solder 500 matings/unmatings 43 straight solder 500 matings/unmatings for harsh environment N :obligatory indication for HE 507 series ←					B																																																																																																																																																																				
C	<u>ELECTRICAL CHARACTERISTICS</u> -NOMINAL CURRENT: 7.5A (SIGNAL CONTACT) -CONTACT RESISTANCE: <=7.3 m Ohms SIGNAL -CONTACT/CONTACT : >=1000 V -CONTACT/GROUND : >=1200 V -INSULATION RESISTANCE: >=5000 MOhms - CLIMATIC CATEGORY: 55/125/21 TEMPERATURE RANGE -55°C TO +125°C DAMP HEAT STEADY STATE 56 DAYS SALT SPRAY 48 HOURS								C																																																																																																																																																																				
D									D																																																																																																																																																																				
E				 I3W3 FOR EXAMPLE					E																																																																																																																																																																				
F				<table><tr><td colspan="4">www.fciconnect.com</td><td colspan="2">surface - ISO 1302 ✓</td><td colspan="2">tolerance std ISO 406 ISO 1101</td><td colspan="2">projection mm</td></tr><tr><td colspan="4"></td><td colspan="2">TOLERANCES UNLESS OTHERWISE SPECIFIED</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="4"></td><td colspan="2">ANGULAR</td><td colspan="2">0.X ±0.3</td><td colspan="2">size A2 Scale 2:1</td></tr><tr><td colspan="4"></td><td colspan="2">LINEAR</td><td colspan="2">0.XX ±0.1</td><td colspan="2"></td></tr><tr><td colspan="4"></td><td colspan="2">0° ±2°</td><td colspan="2">0.XXX ±0.05</td><td colspan="2">ECN LS07-0273</td></tr><tr><td colspan="4"></td><td colspan="2">Product family</td><td colspan="2"></td><td colspan="2">- Spec.ref</td></tr></table> <table><tr><td>rev</td><td>ecn no</td><td>dr</td><td>date</td><td>Dr</td><td>M PESSON</td><td>2006/11/15</td><td colspan="2">FCI</td><td>SUB FEMALE DMW</td><td>deg no</td><td>C01-8637-1751</td><td>Rev.</td></tr><tr><td>A</td><td>LS06-0174</td><td>MPE</td><td>2006/11/15</td><td>Eng</td><td>P LEGARE</td><td>2006/11/15</td><td colspan="2">mixed power straight solder</td><td></td><td></td><td></td><td>B</td></tr><tr><td>B</td><td>LS07-0273</td><td>MPE</td><td>2007/10/30</td><td>Chr</td><td>P LEGARE</td><td>2006/11/15</td><td colspan="2">catalog no</td><td></td><td>CUSTOMER</td><td>sheet 1 of 7</td><td></td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td><td>Appr</td><td>P LEGARE</td><td>2006/11/15</td><td colspan="2"></td><td></td><td></td><td></td><td></td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td><td></td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td><td></td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td><td></td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td><td></td><td></td></tr></table>					www.fciconnect.com				surface - ISO 1302 ✓		tolerance std ISO 406 ISO 1101		projection mm						TOLERANCES UNLESS OTHERWISE SPECIFIED										ANGULAR		0.X ±0.3		size A2 Scale 2:1						LINEAR		0.XX ±0.1								0° ±2°		0.XXX ±0.05		ECN LS07-0273						Product family				- Spec.ref		rev	ecn no	dr	date	Dr	M PESSON	2006/11/15	FCI		SUB FEMALE DMW	deg no	C01-8637-1751	Rev.	A	LS06-0174	MPE	2006/11/15	Eng	P LEGARE	2006/11/15	mixed power straight solder					B	B	LS07-0273	MPE	2007/10/30	Chr	P LEGARE	2006/11/15	catalog no			CUSTOMER	sheet 1 of 7		-	-	-	-	Appr	P LEGARE	2006/11/15							-	-	-	-										-	-	-	-										-	-	-	-										-	-	-	-										F
www.fciconnect.com				surface - ISO 1302 ✓		tolerance std ISO 406 ISO 1101		projection mm																																																																																																																																																																					
				TOLERANCES UNLESS OTHERWISE SPECIFIED																																																																																																																																																																									
				ANGULAR		0.X ±0.3		size A2 Scale 2:1																																																																																																																																																																					
				LINEAR		0.XX ±0.1																																																																																																																																																																							
				0° ±2°		0.XXX ±0.05		ECN LS07-0273																																																																																																																																																																					
				Product family				- Spec.ref																																																																																																																																																																					
rev	ecn no	dr	date	Dr	M PESSON	2006/11/15	FCI		SUB FEMALE DMW	deg no	C01-8637-1751	Rev.																																																																																																																																																																	
A	LS06-0174	MPE	2006/11/15	Eng	P LEGARE	2006/11/15	mixed power straight solder					B																																																																																																																																																																	
B	LS07-0273	MPE	2007/10/30	Chr	P LEGARE	2006/11/15	catalog no			CUSTOMER	sheet 1 of 7																																																																																																																																																																		
-	-	-	-	Appr	P LEGARE	2006/11/15																																																																																																																																																																							
-	-	-	-																																																																																																																																																																										
-	-	-	-																																																																																																																																																																										
-	-	-	-																																																																																																																																																																										
-	-	-	-																																																																																																																																																																										
	I	2	3	4	5	6	7	8																																																																																																																																																																					

