



- ① PLATE OVERALL WITH 0.00127 [.000050] MIN NICKEL, THEN TIP PLATE WITH 0.00076 [.000030] MIN GOLD IN THE MATING AREA.
- ② PLATE OVERALL WITH 0.00127 [.000050] MIN NICKEL, THEN PLATE IN THE MATING AREA AND STRIPE THE INSIDE OF THE WIRE BARREL WITH 0.00076 [.000030] MIN GOLD.
- ③ PLATE OVERALL WITH 0.00127 [.000050] MIN NICKEL, THEN FLASH ENTIRE TERMINAL WITH GOLD, THEN TIP PLATE WITH 0.00076 [.000030] MIN GOLD IN THE MATING AREA.
4. WIRE RANGE: 0.2 — 0.9 mm² [24 — 18 AWG] .
5. INSULATION RANGE: 2.54 [.100] MAX DIA.
6. APPLICATOR TYPE: MINI.
7. DIMENSIONS IN BRACKETS ARE IN INCHES.

	0.30 [.012] BRASS	61116-7
	0.30 [.012] PH BRZ	61116-6
	0.30 [.012] BRASS	61116-5
PRE-TIN	0.30 [.012] PH BRZ	61116-4
-	0.30 [.012] PH BRZ	61116-3
-	0.30 [.012] BRASS	61116-2
PRE-TIN	0.30 [.012] BRASS	61116-1
FINISH	MATERIAL	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T.BECK	2-18-93	 TE Connectivity			
		CHK R. SWING	2-18-93				
DIMENSIONS: MM [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD C. MARTIN	2-24-93	NAME			
	0 PLC ± -	PRODUCT SPEC	PIN, MATE-N-LOK™				
	1 PLC ± -	—	—				
	2 PLC ± 0.25 [.010]	APPLICATION SPEC	—				
	3 PLC ± -	—					
	4 PLC ± -			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
MATERIAL	FINISH	WEIGHT	—	A2	00779	C-61116	—
SEE TABLE	SEE TABLE	CUSTOMER DRAWING			SCALE	SHEET	REV
					5:1	1 of 1	AG 3