

# APC Precision Chip Resistor



- Precision Thin Film Technology
- Wide Resistance Range 1R - 3M
- Precision tolerance down to  $\pm 0.01\%$
- TCR as low as  $\pm 2\text{ppm}/^\circ\text{C}$
- Tape & Reel packaging



- Standard Electrical Specifications
- Tolerance (Code):  $\pm 0.05\%$  (A),  $\pm 0.1\%$  (B),  $\pm 0.25\%$  (C),  $\pm 0.5\%$  (D),  $\pm 1\%$  (F)
- TCR (Code):  $\pm 25\text{ppm}$  (E),  $\pm 50\text{ppm}$  (F)

| Type    | Power Rating at 70°C | Operating Temp Range | Max Operating Voltage | Max Overload Voltage | Tolerance / Resistance Range |                |               |                 |     | TCR (PPM°C) |
|---------|----------------------|----------------------|-----------------------|----------------------|------------------------------|----------------|---------------|-----------------|-----|-------------|
|         |                      |                      |                       |                      | ±0.05%                       | ±0.1%          | ±0.25%        | ±0.5%           | ±1% |             |
| APC0201 | 1/32W                | -55 to +155°C        | 15V                   | 30V                  | N/A                          |                |               | 49.9Ω to 4.99KΩ |     | ±25         |
|         |                      |                      |                       |                      |                              |                |               | 49.9Ω to 33KΩ   |     | ±50         |
| APC0402 | 1/16W                | -55 to +155°C        | 25V                   | 50V                  | 49.9Ω to 12KΩ                | 10Ω to 255KΩ   | 4.7Ω to 511KΩ |                 |     | ±25         |
|         |                      |                      |                       |                      |                              |                |               | ±50             |     |             |
| APC0603 | 1/16W                | -55 to +155°C        | 50V                   | 100V                 | 4.7Ω to 332KΩ                | 4.7Ω to 1MΩ    | 1Ω to 1MΩ     |                 |     | ±25         |
|         |                      |                      |                       |                      |                              |                |               | ±50             |     |             |
| APC0805 | 1/10W                | -55 to +155°C        | 100V                  | 200V                 | 4.7Ω to 1MΩ                  | 4.7Ω to 2MΩ    | 1Ω to 2MΩ     |                 |     | ±25         |
|         |                      |                      |                       |                      |                              |                |               | ±50             |     |             |
| APC1206 | 1/8W                 | -55 to +155°C        | 150V                  | 300V                 | 4.7Ω to 1MΩ                  | 4.7Ω to 2.49MΩ | 1Ω to 2.49MΩ  |                 |     | ±25         |
| APC1210 | 1/4W                 |                      |                       |                      |                              |                |               |                 |     | ±50         |
| APC2010 | 1/4W                 | -55 to +155°C        | 150V                  | 300V                 | 4.7Ω to 1MΩ                  | 4.7Ω to 3MΩ    | 1Ω to 3MΩ     |                 |     | ±25         |
| APC2512 | 1/2W                 |                      |                       |                      |                              |                |               |                 |     | ±50         |

- Special Electrical Specifications
- Tolerance (Code):  $\pm 0.01\%$  (T),  $\pm 0.05\%$  (A),  $\pm 0.1\%$  (B),  $\pm 0.25\%$  (C),  $\pm 0.5\%$  (D),  $\pm 1\%$  (F)
- TCR (Code):  $\pm 2\text{ppm}$  (X),  $\pm 3\text{ppm}$  (Y),  $\pm 5\text{ppm}$  (Z),  $\pm 10\text{ppm}$  (B),  $\pm 15\text{ppm}$  (A)

| Type    | Power Rating at 70°C | Operating Temp Range | Max Operating Voltage | Max Overload Voltage | Resistance Range |               |                 |        |          |          | TCR (PPM°C) |
|---------|----------------------|----------------------|-----------------------|----------------------|------------------|---------------|-----------------|--------|----------|----------|-------------|
|         |                      |                      |                       |                      | ±0.01%           | ±0.05%        | ±0.1%           | ±0.25% | ±0.5%    | ±1%      |             |
| APC0402 | 1/16W                | -55 to +155°C        | 25V                   | 50V                  | 49.9Ω to 4.99KΩ  |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 49.9Ω to 4.99KΩ  |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 49.9Ω to 12KΩ    |               | 49.9Ω to 60KΩ   |        |          | ±10      |             |
|         |                      |                      |                       |                      |                  |               | 49.9Ω to 69.8KΩ |        |          | ±15      |             |
| APC0603 | 1/16W                | -55 to +155°C        | 50V                   | 100V                 | 24.9Ω to 15KΩ    |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 15KΩ    |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 100KΩ   | 4.7Ω to 332KΩ | 4.7Ω to 511KΩ   |        |          | ±10, ±15 |             |
| APC0805 | 1/10W                | -55 to +155°C        | 100V                  | 200V                 | 24.9Ω to 30KΩ    |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 30KΩ    |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 200KΩ   | 4.7Ω to 1MΩ   |                 |        | ±10, ±15 |          |             |
| APC1206 | 1/8W                 | -55 to +155°C        | 150V                  | 300V                 | 24.9Ω to 49.9KΩ  |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 49.9KΩ  |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 499KΩ   | 4.7Ω to 1MΩ   |                 |        | ±10, ±15 |          |             |
| APC1210 | 1/4W                 | -55 to +155°C        | 150V                  | 300V                 | 24.9Ω to 49.9KΩ  |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 49.9KΩ  |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 499KΩ   | 4.7Ω to 1MΩ   |                 |        | ±10, ±15 |          |             |
| APC2010 | 1/4W                 | -55 to +155°C        | 150V                  | 300V                 | 24.9Ω to 100KΩ   |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 100KΩ   |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 499KΩ   | 4.7Ω to 1MΩ   |                 |        | ±10, ±15 |          |             |
| APC2512 | 1/2W                 | -55 to +155°C        | 150V                  | 300V                 | 24.9Ω to 100KΩ   |               |                 | N/A    |          |          | ±2, ±3      |
|         |                      |                      |                       |                      | 24.9Ω to 100KΩ   |               |                 |        |          |          | ±5          |
|         |                      |                      |                       |                      | 24.9Ω to 499KΩ   | 4.7Ω to 1MΩ   |                 |        | ±10, ±15 |          |             |

ARCOL UK Limited,  
Threemilestone Ind. Estate,  
Truro, Cornwall, TR4 9LG, UK.  
T +44 (0) 1872 277431  
F +44 (0) 1872 222002  
E sales@arcolresistors.com

[www.arcolresistors.com](http://www.arcolresistors.com)

The information contained herein does not form part of a contract and is subject to change without notice. ARCOL operate a policy of continual product development, therefore, specifications may change.

It is the responsibility of the customer to ensure that the component selected from our range is suitable for the intended application. If in doubt please ask ARCOL.


## Characteristics

| Item                  | Tol. ≤ 0.05%          | Tol. > 0.05%           | Method                                                             |
|-----------------------|-----------------------|------------------------|--------------------------------------------------------------------|
| Short Time Overload   | $\Delta R \pm 0.05\%$ | $\Delta R \pm 0.02\%$  | RCWV*2.5 or Max. Overload Voltage - whichever is lower for 5 secs. |
| Insulation Resistance | > 1000 MΩ             |                        | Apply 100V dc for 1 minute                                         |
| Endurance             | $\Delta R \pm 0.05\%$ | $\Delta R \pm 0.02\%$  | 70 ±2°C RCWV for 1000 hours with 1.5 hrs ON and 0.5 hrs OFF        |
| Thermal Shock         | $\Delta R \pm 0.05\%$ | $\Delta R \pm 0.025\%$ | -55 to +155°C, 100 Cycles                                          |
| Low Temp Operation    | $\Delta R \pm 0.05\%$ | $\Delta R \pm 0.2\%$   | 1 hour, -65°C followed by 45 mins of RCWV                          |

\*RCWV (Rated Continuous Working Voltage) =  $\sqrt{P \cdot R}$  or Max. Operating Voltage - whichever is lower

## Dimensions (mm)

| Type    | L          | W          | T          | D1         | D2         |
|---------|------------|------------|------------|------------|------------|
| APC0201 | 0.58 ±0.05 | 0.29 ±0.05 | 0.23 ±0.05 | 0.12 ±0.05 | 0.15 ±0.05 |
| APC0402 | 1.00 ±0.05 | 0.50 ±0.05 | 0.30 ±0.05 | 0.20 ±0.05 | 0.20 ±0.05 |
| APC0603 | 1.55 ±0.10 | 0.80 ±0.10 | 0.45 ±0.10 | 0.30 ±0.20 | 0.30 ±0.20 |
| APC0805 | 2.00 ±0.15 | 1.25 ±0.15 | 0.55 ±0.10 | 0.30 ±0.20 | 0.40 ±0.20 |
| APC1206 | 3.05 ±0.15 | 1.55 ±0.15 | 0.55 ±0.10 | 0.42 ±0.20 | 0.35 ±0.25 |
| APC1210 | 3.10 ±0.15 | 2.40 ±0.15 | 0.55 ±0.10 | 0.40 ±0.20 | 0.55 ±0.25 |
| APC2010 | 4.90 ±0.15 | 2.40 ±0.15 | 0.55 ±0.10 | 0.60 ±0.30 | 0.50 ±0.25 |
| APC2512 | 6.30 ±0.15 | 3.10 ±0.15 | 0.55 ±0.10 | 0.60 ±0.30 | 0.50 ±0.25 |




## Reel Dimensions (mm)

| Size   | ØA       | ØB      | ØC        | W         | T         | Qty Per Reel |
|--------|----------|---------|-----------|-----------|-----------|--------------|
| 0201*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 10,000       |
| 0402*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 10,000       |
| 0603*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 5,000        |
| 0805*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 5,000        |
| 1206*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 5,000        |
| 1210*  | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 9.5 ±1.0  | 11.5 ±1.0 | 5,000        |
| 2010** | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 13.5 ±1.0 | 15.5 ±1.0 | 4,000        |
| 2512** | 178 ±1.0 | 60 ±1.0 | 13.5 ±0.7 | 13.5 ±1.0 | 15.5 ±1.0 | 4,000        |

\* Paper Tape

\*\* Plastic Embossed Tape



## Ordering Procedure


Standard Resistor: Series, Size, Tol Code, Resistance Value, TCR Code

Eg: APC0603A100RB  
 100Ω  
 ±0.05%  
 1/16 watt  
 (0603 size)

Tol: ±0.01% (T), ±0.05% (A), ±0.1% (B), ±0.25% (C), ±0.5% (D), ±1% (F)

TCR: ±2ppm (X), ±3ppm (Y), ±5ppm (Z), ±10ppm (B), ±15ppm (A), ±25ppm (E), ±50ppm (F)

## Derating Curve



ARCOL UK Limited,  
 Threemilestone Ind. Estate,  
 Truro, Cornwall, TR4 9LG, UK.  
 T +44 (0) 1872 277431  
 F +44 (0) 1872 222002  
 E sales@arcolresistors.com

[www.arcolresistors.com](http://www.arcolresistors.com)

The information contained herein does not form part of a contract and is subject to change without notice. ARCOL operate a policy of continual product development, therefore, specifications may change.

It is the responsibility of the customer to ensure that the component selected from our range is suitable for the intended application. If in doubt please ask ARCOL.