

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>01</td><td>REVISED</td><td>02/23/95</td><td>AD</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	01	REVISED	02/23/95	AD																																												
			REVISIONS																																																											
			REV	DESCRIPTION	DATE	APPROVED																																																								
01	REVISED	02/23/95	AD																																																											
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348</td><td>Temperature Rating -65°C To +165°C</td></tr><tr><td>Frequency Range (GHz) DC - 18</td><td>FIG 310.2</td><td>Vibration - MIL-STD-202, Method 204, Condition D, 20G's</td></tr><tr><td>VSWR 1.06 + (.010 F(GHz))</td><td>Recommended Mating Torque N/A</td><td>Shock - MIL-STD-202, Method 107, Condition B</td></tr><tr><td>Insertion Loss (dB MAX) .04 √F(GHz)</td><td>Mating Characteristics:</td><td>Thermal shock MIL-STD-202, Method 107, Condition B</td></tr><tr><td>RF Leakage (dB MIN) -(100 - F(GHz))</td><td>Insertion (MAX Lbs) 3.0</td><td>Except High Temp 115°C</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 333</td><td>Withdrawal (MIN Oz) 1.0</td><td>Moisture Resistance - MIL-STD-202, Method 106</td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) 1000 @ sea level</td><td>Force To Engage (In/Lbs MAX) 2.0</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Force To Disengage (In/Lbs MAX) 2.0</td><td>Leak Test - MIL-STD-202, Method 112, Condition C, Procedure 1, 1 X 10⁻⁸ CC/SEC</td></tr><tr><td>Center Contact 10.0</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial 6.0 Lbs</td><td></td></tr><tr><td>RF High Potential (VRMS MIN @ 5 MHz) 667 @ sea level</td><td>Radial N/A</td><td></td></tr><tr><td>I.R.(Megohms) 5000</td><td>Weight (Grams) T.B.D.</td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348	Temperature Rating -65°C To +165°C	Frequency Range (GHz) DC - 18	FIG 310.2	Vibration - MIL-STD-202, Method 204, Condition D, 20G's	VSWR 1.06 + (.010 F(GHz))	Recommended Mating Torque N/A	Shock - MIL-STD-202, Method 107, Condition B	Insertion Loss (dB MAX) .04 √F(GHz)	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107, Condition B	RF Leakage (dB MIN) -(100 - F(GHz))	Insertion (MAX Lbs) 3.0	Except High Temp 115°C	Corona, 70,000 Ft (VRMS MIN) 333	Withdrawal (MIN Oz) 1.0	Moisture Resistance - MIL-STD-202, Method 106	Dielectric Withstanding Voltage (VRMS MIN) 1000 @ sea level	Force To Engage (In/Lbs MAX) 2.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Contact Resistance (Milliohms MAX)	Force To Disengage (In/Lbs MAX) 2.0	Leak Test - MIL-STD-202, Method 112, Condition C, Procedure 1, 1 X 10 ⁻⁸ CC/SEC	Center Contact 10.0	Center Contact Captivation		Outer Contact 2.0	Axial 6.0 Lbs		RF High Potential (VRMS MIN @ 5 MHz) 667 @ sea level	Radial N/A		I.R.(Megohms) 5000	Weight (Grams) T.B.D.		<table><tr><td>HOUSING</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATED PER ASTM-A380</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>CONTACT EXT BUSHING</td><td>IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 (KOVAR)</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>HERMETIC SEAL</td><td>GLASS BEAD</td><td>N/A</td></tr><tr><td>GASKET</td><td>CONDUCTIVE SILVER/SILICONE ELASTOMERS</td><td>N/A</td></tr></table>			HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATED PER ASTM-A380	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	CONTACT EXT BUSHING	IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 (KOVAR)	GOLD PLATE PER MIL-G-45204	HERMETIC SEAL	GLASS BEAD	N/A	GASKET	CONDUCTIVE SILVER/SILICONE ELASTOMERS	N/A
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																												
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348	Temperature Rating -65°C To +165°C																																																												
Frequency Range (GHz) DC - 18	FIG 310.2	Vibration - MIL-STD-202, Method 204, Condition D, 20G's																																																												
VSWR 1.06 + (.010 F(GHz))	Recommended Mating Torque N/A	Shock - MIL-STD-202, Method 107, Condition B																																																												
Insertion Loss (dB MAX) .04 √F(GHz)	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107, Condition B																																																												
RF Leakage (dB MIN) -(100 - F(GHz))	Insertion (MAX Lbs) 3.0	Except High Temp 115°C																																																												
Corona, 70,000 Ft (VRMS MIN) 333	Withdrawal (MIN Oz) 1.0	Moisture Resistance - MIL-STD-202, Method 106																																																												
Dielectric Withstanding Voltage (VRMS MIN) 1000 @ sea level	Force To Engage (In/Lbs MAX) 2.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																												
Contact Resistance (Milliohms MAX)	Force To Disengage (In/Lbs MAX) 2.0	Leak Test - MIL-STD-202, Method 112, Condition C, Procedure 1, 1 X 10 ⁻⁸ CC/SEC																																																												
Center Contact 10.0	Center Contact Captivation																																																													
Outer Contact 2.0	Axial 6.0 Lbs																																																													
RF High Potential (VRMS MIN @ 5 MHz) 667 @ sea level	Radial N/A																																																													
I.R.(Megohms) 5000	Weight (Grams) T.B.D.																																																													
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATED PER ASTM-A380																																																												
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																												
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																												
CONTACT EXT BUSHING	IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 (KOVAR)	GOLD PLATE PER MIL-G-45204																																																												
HERMETIC SEAL	GLASS BEAD	N/A																																																												
GASKET	CONDUCTIVE SILVER/SILICONE ELASTOMERS	N/A																																																												
<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°</td><td>DRAWN BY BB DATE 7/1/94 CHECKED BY APPD BY</td><td>AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td>These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASS'Y PROCEDURE 408-04866 (20-741) NO. AP.</td><td>TITLE OSM TWO-HOLE FLANGE MOUNT JACK RECEPTACLE WITH EMI/RFI GASKET SIZE B CODE IDENT NO. 26805 2052-3357-02 REV 01 SCALE 5:1 SHEET 1 OF 1</td></tr></table>			COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°	DRAWN BY BB DATE 7/1/94 CHECKED BY APPD BY	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE 408-04866 (20-741) NO. AP.	TITLE OSM TWO-HOLE FLANGE MOUNT JACK RECEPTACLE WITH EMI/RFI GASKET SIZE B CODE IDENT NO. 26805 2052-3357-02 REV 01 SCALE 5:1 SHEET 1 OF 1																																																			
COMPONENT	MATERIAL	FINISH																																																												
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°	DRAWN BY BB DATE 7/1/94 CHECKED BY APPD BY	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																												
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE 408-04866 (20-741) NO. AP.	TITLE OSM TWO-HOLE FLANGE MOUNT JACK RECEPTACLE WITH EMI/RFI GASKET SIZE B CODE IDENT NO. 26805 2052-3357-02 REV 01 SCALE 5:1 SHEET 1 OF 1																																																												