

Coaxial Panel Connector 22_BNC-50-0-3/133_N

Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 4 GHz |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 500 |
| Weight | 0.0111 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Gasket | VMQ (Silicone rubber) | |
| Fastening nut | Brass | SUCOPLATE (R) Plating |
| Washer | Bronze | SUCOPLATE (R) Plating |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00010695 |
| Catalogue drawing | DCA-00010697 |
| Mounting hole | DOU-00010411 |

Ordering Information

| | |
|----------------------|----------------------|
| Single package | 22_BNC-50-0-3/133_NE |
| Bulk 100 pcs package | 22_BNC-50-0-3/133_NH |

Remarks

Front mount chassis connector With panel seal

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[22_BNC-50-0-3/133_NH](#)