

DOUBLE SIDE TAPE

GRILL SCREEN

8-Ø2.00

PCB Ø9.00

Ø3.50

8-45.0°

DOUBLE SIDE TAPE

PORON

GRILL SCREEN

BACK SCREEN

Ø17.00

Ø16.30

Ø13.00

Ø9.90

3.90

3.40

2.00

1.70

Diagram illustrating the back view of the LED light fixture, showing mounting holes and dimensions:

- BACK SCREEN
- R6.50
- 2- $\varnothing 1.00$
- 8- $\varnothing 1.50$
- 5-25.0°
- 2-21.5°
- 2-20.0°
- 100.0°
- XX/X
- Silk Screen Marking
- Date Code Marking "10 / F"
- Year $\left\{ \begin{array}{l} \text{10} = 2010 \\ \text{F} = \text{Jun.} \end{array} \right.$
- Month

Specifications			Notes	Revision History					
Description	Value	Unit		Version	Description		Date	Approved	
Shape	Round		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		2/5/2014	J.S	
Resonant Frequency	800	(Hz)							
Frequency Range	250 ~ 10,000	(Hz)							
SPL @ 10cm	90	(dBA)							
Impedance	8	(Ohm)							
Cone Material	Mylar								
Nominal Power	0.8	(W)							
Max Power	1	(W)							
Mount Type	Flush Mount								
Operating Temperature	- 30 ~ + 70	°C							
Storage Temperature	- 30 ~ + 70	°C		Drawn by	Date	Checked by	Date	Approved by	Date
Weight	1.5	(g)		G.W.	10/31/2013	C.E.	10/21/2013	J.S	2/5/2014
			DB UNLIMITED	Dynamic Speaker			SM170808-1		