

30mm Selector Switch Metal Operators



Certified for
NEMA Type 4X
12 environment.

Selector Maintained & Momentary



Other colors available upon request. Please contact Altech for further information and part numbers.

Color

Cat No.

2 Position Maintained

■ Black	AS2-2P
---------	--------

3 Position Maintained


■ Black	AS2-3P
---------	--------

2 Position Momentary

■ Black	AS2-2PSR
---------	----------

Key Selector Switch

Keyed Alike



To be used for applications where single or multiple operators are used, but the same key configurations are required. Standard key selector switches have the same key configuration (Cat. No. KY30).

Function

Key Removal

Cat No.

2 Position

Maintained	↙↘	Left/Right	AK2-2PB
Momentary	↙↘	Left	AK2-2POSR
Maintained	↙↘	Right	AK2-2PI
Maintained	↙↘	Left	AK2-2PO

3 Position

Maintained	↙↘↗	Left/Right	AK2-3PB
Maintained	↙↘↗	Center	AK2-3PC




Replacement Key

KY30

Key Selector Switch

Keyed Differently



To be used for applications where multiple operators are used, but different key configurations are required. Each cat. no. have different key configurations.

Function

Key Removal

Cat No.

2 Position

Maintained	↙↘	Left	AK2-2PO-KD
Momentary	↙↘	Left	AK2-2PO-KD1
Maintained	↙↘	Left	AK2-2PO-KD2
Maintained	↙↘	Left	AK2-2PO-KD4
Maintained	↙↘	Left	AK2-2PO-KD5

3 Position


Maintained	↙↘↗	Center	AK2-3PC-KD
Maintained	↙↘↗	Center	AK2-3PC-KD1
Maintained	↙↘↗	Center	AK2-3PC-KD2
Maintained	↙↘↗	Center	AK2-3PC-KD3

30mm Selector Switch Metal Operators


Dimensional Drawings

All dimensions shown in millimeters.
To convert to inches multiply by 0.03937

Flush Maintained and Momentary



Key Selector



Contact Elements

Description

1 Normally Open + 1 Normally Closed
Silver Contacts


Cat. No.

S11

2 Normally Open + 2 Normally Closed
Silver Contacts

S11 + S12


For additional contacts, see diagram at right.



Contact Installation Screws

Type	Dimensions	Used with
SC25	M4 x 25 mm	S11
SC45	M4 x 45 mm	S11 + S12
SC65	M4 x 65 mm	2x S11 + S12
SC90	M4 x 90 mm	2x S11 + 2x S12

* When using more than two contact blocks, additional screws must be purchased separately (SC65 and SC90).



Exploded Assembly View

