10119191 - X 0 E - X X X LF

- LEAD-FREE DESIGNATION ONLY WITH APPLICABLE PLATING CODES
- 8-COLUMN DIFFERENTIAL SIGNAL

LETTER	PERFORMANCE-BASED PLATING (SEE NOTE 2)	
	TARGET APPLICATION	LEAD-FREE (LF)
B	TELCORDIA CO	NO
C	TELCORDIA UE	NO
D	TELCORDIA CO	YES
E	TELCORDIA UE	YES

NUMBER	GUIDE PIN STYLE, HEIGHT
0	STANDARD GUIDE PIN MACHINED, 31.6mm
4	STANDARD GUIDE PIN MACHINED, 25.7mm

NUMBER	CONTACT MATING WIPE LENGTH		COMPLIANT PIN DRILL SIZE
	SIGNAL	GROUND	
1	2	4	Ø0.55 [0.0217"]
2	3	4	Ø0.55 [0.0217"]
3	2	4	Ø0.45 [0.0177"]
4	3	4	Ø0.45 [0.0177"]
5	2	3	Ø0.55 [0.0217"]
6	3	3	Ø0.55 [0.0217"]
7	2	3	Ø0.45 [0.0177"]
8	3	3	Ø0.45 [0.0177"]

MODULE DESCRIPTION	LETTER DESIGNATION REPRESENTED IN DASH NUMBER								BASE MODULE
LEFT POLARIZING GUIDANCE MODULE (SEE SHEET 3)	J	A	B	C	D	E	F	G	H	
										
RIGHT POLARIZING GUIDANCE MODULE (SEE SHEET 4)	Y	P	Q	R	S	T	U	V	W	
										
OPEN MODULE (TWO WALL) (SEE SHEET 2)	0 (ZERO)									
LEFT WALL MODULE (SEE SHEET 5)	L									
RIGHT WALL MODULE (SEE SHEET 6)	M									
FOUR WALL MODULE (SEE SHEET 7)	I (ONE)									

TABLE 1: OPTIONAL PCB HOLE SIZE (SEE NOTE 11)

	GROUNDED	UNGROUNDED
FINISHED	Ø2.35-2.55	Ø2.35-2.55
PAD	Ø5.50	N/A
PLATED	YES	NO
DRILL (mm/in)	2.58/.1015	2.44/.096

TABLE 2: OPTIONAL SCREW TYPE (SEE NOTE 10)

SCREW P/N	DESCRIPTION	BOARD THICKNESS
10091790-002LF	#2.56 X .375" PHILIPS PANHEAD W/SQ CONICAL WASHER	1.60 - 5.00
10091790-003LF	#2.56 X .500" PHILIPS PANHEAD W/SQ CONICAL WASHER	5.00 - 10.00

© 2016 AFCI

spec ref	-	dr	Roger Ng	2011/11/22	projection	MM	size A2	scale 4:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED	eng	Michael Song	2016/06/01			ecn no	ELX-DG-24191-1
		chr	Heaven Cen	2016/06/08			rel level	Released
		appr	Pei-Ming Zheng	2016/06/15	product family	XCEDE		
surface ASME Y14.5	linear 0.X ±0.2; 0.XX ±0.10; 0.XXX ±0.050; angular 0° ±2°	Amphenol FCi	title	MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR	dwg no	10119191	rev	C
			cat. no.	-	Product - Customer Drw		sheet 1 of 8	

OPEN (2- WALL) MODULE







PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1







spec ref -				dr	Roger Ng	2011/11/22	projection	MM	size A2 / scale 4:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Michael Song	2016/06/01			ecn no ELX-DG-24191-1
				chr	Heaven Cen	2016/06/08			
				appr	Pei-Ming Zheng	2016/06/15	product family XCEDE		rel level Released
surface ASME Y14.5	linear	0.X	±0.2	Amphenol FCi	title: MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR			dwg no 10119191	rev C
		0.XX	±0.10						
		0.XXX	±0.050						
	angular	0°	±2°		cat. no. -		Product - Customer Drw		sheet 2 of 8

© 2016 AFCI

LEFT POLARIZING/GUIDE MODULE











PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1



ASSEMBLY BASE CONFIGURATION END DASH NO.	GUIDE PIN	POLARIZING KEY
	DIM 'R'	DIM 'S'
-X0X	31.6mm	22.8mm
-X4X	25.7mm	20.0mm

spec ref -			dr	Roger Ng	2011/11/22	projection	MM	size A2	scale 5:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01			ecn no	ELX-DG-24191-1
			chr	Heaven Cen	2016/06/08				
			appr	Pei-Ming Zheng	2016/06/15	product family	XCEDE	rel level	Released
surface ASME Y14.5	linear	0.X	±0.2	Amphenol FCi	title	MODULE ASSEMBLY		dwg no	10119191	rev	C
		0.XX	±0.10			VERTICAL HEADER, 8-COLUMN, 3-PAIR					
		0.XXX	±0.050								
	angular	0°	±2°		cat. no.	-	Product - Customer Drw		sheet 3 of 8		

© 2016 AFCI

RIGHT POLARIZING/GUIDE MODULE







PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1







ASSEMBLY BASE CONFIGURATION END DASH NO.	GUIDE PIN DIM 'R'	POLARIZING KEY DIM 'S'
-X0X	31.6mm	22.8mm
-X4X	25.7mm	20.0mm

spec ref	-		dr	Roger Ng	2011/11/22	projection	MM
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01		
			chr	Heaven Cen	2016/06/08		
			appr	Pei-Ming Zheng	2016/06/15		
surface ASME Y14.5	linear	0.X ±0.2	Amphenol FCi	title	MODULE ASSEMBLY	dwg no	10119191
		0.XX ±0.10			VERTICAL HEADER, 8-COLUMN, 3-PAIR		rev C
		0.XXX ±0.050					
	angular	0° ±2°		cat. no.	-	Product - Customer Drw	sheet 4 of 8

size	scale
A2	4:1

ecn no ELX-DG-24191-1
rel level **Released**
product family XCEDE

© 2016 AFCI

LEFT WALL MODULE







PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1







spec ref -			dr	Roger Ng	2011/11/22	projection	MM	size A2 / scale 4:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01			
			chr	Heaven Cen	2016/06/08			ecn no ELX-DG-24191-1
			appr	Pei-Ming Zheng	2016/06/15	product family XCEDE		rel level Released
surface ASME Y14.5	linear	0.X	±0.2	Amphenol FCi	title	MODULE ASSEMBLY	dwg no 10119191	rev C
		0.XX	±0.10			VERTICAL HEADER, 8-COLUMN, 3-PAIR		
		0.XXX	±0.050					
	angular	0°	±2°		cat. no. -	Product - Customer Drw		sheet 5 of 8

© 2016 AFCI

Creo File - REV.E - 2016-02-12

PDS: Rev :C STATUS: Released Printed: Jun 15, 2016

RIGHT WALL MODULE







PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1







spec ref	-		dr	Roger Ng	2011/11/22	projection	MM
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01		
			chr	Heaven Cen	2016/06/08		
			appr	Pei-Ming Zheng	2016/06/15		
surface ASME Y14.5	linear	0.X ±0.2	Amphenol FCi	title	MODULE ASSEMBLY	dwg no	10119191
		0.XX ±0.10			VERTICAL HEADER, 8-COLUMN, 3-PAIR		
		0.XXX ±0.050					
	angular	0° ±2°		cat. no.	-	Product - Customer Drw	sheet 6 of 8

size	A2	scale	4:1	rev	C				
ecn no	ELX-DG-24191-1								
rel level	Released								

© 2016 AFCI

FOUR WALL MODULE







PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1







spec ref -			dr	Roger Ng	2011/11/22	projection	MM	size A2 / scale 4:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01			ecn no ELX-DG-24191-1
			chr	Heaven Cen	2016/06/08			
			appr	Pei-Ming Zheng	2016/06/15	product family XCEDE		rel level Released
surface ASME Y14.5	linear	0.X	±0.2	Amphenol FCi	title: MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR		dwg no 10119191	rev C
		0.XX	±0.10					
		0.XXX	±0.050					
	angular	0°	±2°		cat. no. -	Product - Customer Drw		sheet 7 of 8

© 2016 AFCI

NOTES:

1. CONNECTOR MATERIALS
   SHROUD: HIGH-TEMP THERMOPLASTIC, GRAY, UL94V-0
   CONTACTS: HIGH PERFORMANCE COPPER ALLOY

(2) CONTACT PLATING:

   SEPARABLE INTERFACE: PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12 588, INCLUDING THE TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE (CO) OR UNCONTROLLED ENVIRONMENT (UE) TEST SEQUENCE AS NOTED IN P/N TREE.

   PRESS-FIT TAILS: TIN OVER NICKEL (LF), OR TIN-LEAD ALLOY OVER NICKEL (NON-LF). SEE P/N TREE.

3. PRODUCT SPECIFICATION: GS-12-588

4. APPLCATION SPECIFICATION: GS-20-121

(5) PRODUCT MARKING (PART NUMBER AND LOT CODE) ON THESE SURFACES.

6. HOUSING MUST WITHSAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED, OR VAPOR-PHASE REFLOW OVEN.

7. PACKAGING MEETS GS-14-920 LEAD-FREE LABELING SPECIFICATION.

(8) NOTCH INDICATES "ROW A" SIDE OF CONNECTOR.

(9) SEE APPLICATION SPECIFICATION FOR ROUTING GUIDELINES, ADDITIONAL PTH GUIDELINES, MATED DIMENSIONS, GUIDE PN SELECTION, ETC.

(10) SCREW IS OPTIONAL AND ENGAGES WITH BOTTOM OF GUIDE-PIN FROM BENEATH THE PCB FOR ADDITIONAL GUIDE-PIN SUPPORT.

(11) OPTINAL HOLE LOCATION FOR GROUNDED PIN OR ADDITIONAL GUIDE-PIN SUPPORT. SEE TABLE 1 ON SHEET 1 FOR ADDITIONAL DETAILS.

(12) TAIL LENGTH=1.3mm FOR ∅0.55[0.0217"]COMPLIANT PIN DRILL
TAIL LENGTH=1.5mm FOR ∅0.45[0.0177"]COMPLIANT PIN DRILL

TABLE 3: PTH AND PAD SIZES WITH REFERENCE TO COMPLIANT PIN DRILL

COMPLIANT PIN DRILL	PTH	PAD
∅0.55 [0.0217"]	∅0.45±0.05	∅0.85
∅0.45 [0.0177"]	∅0.36±0.05	∅0.75



DETAIL A
SCALE 12:1

spec ref -			dr	Roger Ng	2011/11/22	projection	MM	size A2 / scale 3:1
tolerance std - ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Michael Song	2016/06/01			
			chr	Heaven Cen	2016/06/08			ecn no ELX-DG-24191-1
			appr	Pei-Ming Zheng	2016/06/15	product family -		rel level Released
surface - ASME Y14.5	linear	0.X ±0.2	Amphenol FCi	title	MODULE ASSEMBLY	dwg no 10119191		rev C
		0.XX ±0.10			VERTICAL HEADER, 8-COLUMN, 3-PAIR			
		0.XXX ±0.050						
	angular	0° ±2°		cat. no. -	Product - Customer Drw			sheet 8 of 8

© 2016 AFCI