



**Bemerkung:**

1. Material und Beschichtung:
  - Metallkappe: Kupferlegierung, vernickelt
  - Kugellkette: Kupferlegierung, vernickelt
  - Schraube: Kupferlegierung, vernickelt
  - Dichtung: Silikon; Shore 40 A; Farbe: weiß
2. Betriebstemperatur: -40°C to +85°C
3. RoHS verträglich

**Notes:**

1. Material and finish:
  - Metal cover: Copper alloy, Nickel plated
  - Ball chain: Copper alloy, Nickel plated
  - Screw: Copper alloy, Nickel plated
  - Cover gasket: silicon; Shor 40 A; colour: white
2. Operating Temperature: -40°C to +85°C
3. RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH  DO NOT ALTER CAD DRAWING BY HAND				Tolerance Unless otherwise specified		scale: 2:1	
				0. ±0,2 0.0 ±0,1 0.00 ±0,05		material: see notes	
				dim. in mm		title: Protective Cover Assembly Kit	
				date		name	
drawn 02.03.2012		B.Strakerjahn		Metal Version for use on a male 7/8" connector			
appd. 02.03.2012		J.Kühle					
norm							
d-old				dwg no:		DIN-A3	
2 x b		Ä 4832		09.07.2013		sh: 1	
a		Original				41K1A454	
rev.		description		date		name	
						part no: 41-01430	

