



SIGN	DATE	DESCRIPTION	APPROVER
△	01/30.07	Soldering temperature changed from 245° to 250°	Tason
△	01/30.07	Part NO is Changed	Tason
△	03/08.08	Dimension from 10.0mm to 10.16mm	Aaron
△	01/08.09	Terminal screw changed from M2.5 to M3.0	Kind
△	01/08.09	Safety Approval:cULus	Kind

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
 - Item 2 Clamp : Brass , Ni plated
 - Item 3 Wire guard solder pin , Brass , Tin plated
 - Item 4 Terminal screw: Steel Zinc plating"-slot type

- Electrical
- Voltage rating: 300V
 - Current rating: 10A
 - Torque(Lb-In): 3.5
 - △ ● Screw: M3.0
 - Wrie range:
 - SOLID WIRE(AWG): 16-26
 - Stranded wire(AWG): 16-26
 - Wire strip length: 6-7mm
 - Withstanding Voltage:1.6kv
 - Operating temperature: -40°C to +115°C
 - △ ● Soldering reliability: 250°C±10°C/5 Sec
 - △ ● Safety Approval: cULus

△ YS xx 2 1 x 0 xxxx G

04 2x2 CONTACTS	0 Black	0000:"@"Logo (Standard) RoHS
06 2x3 CONTACTS	5 Green	000A:"ANYTEK"Logo Pb<40,000ppm
... ..	6 Blue	Any special item by customer request,
48 2x24 CONTACTS	8 Grey	please contact sales department.

Poles	2x2	2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10	2x11	2x12	2x13
Dim L	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96	66.04
Dim B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96
TOL	±0.15					±0.20					±0.25	
Poles	2x14	2x15	2x16	2x17	2x18	2x19	2x20	2x21	2x22	2x23	2x24	
Dim L	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	121.92	
Dim B	66.04	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	
TOL	±0.25					±0.30						

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		YS-5.08 Series Stackable					
PART NO.		YSxx21x0xxxxG			DWG NO.		8YS0001
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Kind	Kind			X. ±0.50
			2009.01.08	2009.01.08			X.X ±0.30
					SHEET: 01/01		X.XX ±0.10
							X° ±1°