



SIGN	DATE	DESCRIPTION	APPROVER
△	01/30.07	Soldering temperature changed from 245° to 250°	Tason
△	01/30.07	Part NO is Changed	Tason
△	03/08.08	Dimension from 10.0mm to 10.16mm	Aaron
△	01/08.09	Terminal screw changed from M2.5 to M3.0	Kind
△	01/08.09	Safety Approval:cULus	Kind

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
- Item 2 Clamp : Brass , Ni plated
- Item 3 Wire guard solder pin , Brass , Tin plated
- Item 4 Terminal screw: Steel Zinc plating"--slot type

Electrical

- Voltage rating: 300V
- Current rating: 10A
- Torque(Lb-In): 3.5
- △ ● Screw: M3.0
- Wrie range:
- SOLID WIRE(AWG): 16-26
- Stranded wire(AWG): 16-26
- Wire strip length: 6-7mm
- Withstanding Voltage:1.6kv
- Operating temperature: -40°C to +115°C
- △ ● Soldering reliability: 250°C±10°C/5 Sec
- △ ● Safety Approval: cULus

△ YS xx 2 1 x 0 xxxx G

04 2x2 CONTACTS	0 Black	0000:"@Logo (Standard)	RoHS
06 2x3 CONTACTS	5 Green	000A:"ANYTEK"Logo	Pb<40,000ppm
... ..	6 Blue	Any special item by customer request, please contact sales department.	
48 2x24 CONTACTS	8 Grey		

Poles	2x2	2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10	2x11	2x12	2x13	
Dim L	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96	66.04	
Dim B	5.08	10.16	15.24	20.32	25.40	30.48	35.56	40.64	45.72	50.80	55.88	60.96	
TOL	±0.15					±0.20					±0.25		
Poles	2x14	2x15	2x16	2x17	2x18	2x19	2x20	2x21	2x22	2x23	2x24		
Dim L	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84	121.92		
Dim B	66.04	71.12	76.20	81.28	86.36	91.44	96.52	101.60	106.68	111.76	116.84		
TOL	±0.25					±0.30							

ANYTEK					CUSTOMER COPY		
					<small>ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD</small>		
TITLE	YS-5.08 Series Stackable						
PART NO.	YSxx21x0xxxxG			DWG NO.	8YS0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
					UNIT: mm	X. ±0.50	
		Kind 2009.01.08	Kind 2009.01.08		SCALE: NONE	X.X ±0.30	
					SHEET: 01/01	X.XX ±0.10	
					REV.: F	X° ±1°	