

.050" 28 AWG STRANDED, MASS TERMINATABLE, HALOGEN FREE PO/PO

HF659/XX XX XX

- BLANK = STANDARD
SF = SPLICE FREE

NOTE:
AVAILABLE IN STANDARD 275FT ROLLS. CONTACT 3M
FOR AVAILABILITY OF ADDITIONAL CONDUCTOR COUNTS
AND/OR CUSTOM ROLL LENGTHS.

2 PHYSICAL :

MARKING: STANDARD: NONE
CONDUCTORS: 28 AWG, 7 X 36 AWG [7 X Ø.127] TINNED STRANDED COPPER
SHIELDING: .001 [.03] THICK ALUMINUM/POLYESTER FILM FOIL AND 90%
COVERAGE TINNED COPPER BRAID.

2 ELECTRICAL :

	UNBALANCED	BALANCED
CHARACTERISTIC IMPEDANCE:	54Ω	107Ω
CAPACITANCE:	28.7 pF/ft [84.2 pF/m]	14.4 pF/ft [47.2 pF/m]
INDUCTANCE:	.08μH/ft [.27μH/m]	.16μH/ft [.52μH/m]
PROPAGATION DELAY:	1.55 ns/ft [4.95 ns/m]	1.54 ns/ft [4.95 ns/m]
VELOCITY OF PROPAGATION:	66%	66%

NOTE: UNBALANCED IS MEASURED BETWEEN GROUND-SIGNAL-GROUND CONDUCTORS.
BALANCED IS MEASURED BETWEEN CONDUCTORS WITHIN A PAIR.
"MEASURED VALUES ARE TYPICAL"

2 ENVIRONMENTAL :

TEMPERATURE RATING: -40°C TO +105°C (EIA-364-32G, METHOD A, TEST CONDITION 2)
-15°C TO +75°C (UL TEMPERATURE RATING)

FLAMMABILITY RATING: INTERNAL: HORIZONTAL FLAME PER UL758
EXTERNAL: CABLE FLAME (VERTICAL) PER UL758

HALOGEN FREE IS DEFINED AS BOTH 1) NO HALOGEN COMPOUNDS THAT ARE INTENTIONALLY ADDED TO THE PRODUCT OR USED IN THE MANUFACTURING PROCESS FOR THE PRODUCT AND 2) ANY IMPURITIES PRESENT ARE LESS THAN 900ppm BROMINE, LESS THAN 900ppm CHLORINE AND/OR LESS THAN 1500ppm TOTAL BROMINE AND CHLORINE. THE LATTER ARE THE LEVELS SET FORTH IN CERTAIN INDUSTRY STANDARDS FOR PRINTED CIRCUIT BOARDS, SUCH AS THE INTERNATIONAL ELECTROTECHNICAL COMMISSION (IEC) 61249-2-21 STANDARDS. THIS INFORMATION REPRESENTS 3M'S KNOWLEDGE AND BELIEF WHICH MAY BE BASED IN WHOLE OR IN PART ON INFORMATION PROVIDED BY 3RD PARTY SUPPLIERS TO 3M.

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373



INCH [MM]			
TOLERANCE - UNLESS NOTED			
	.X	.XX	.XXX
[INCH]	±.1	±.05	±.010
[] = DIM. FOR REFERENCE ONLY			

DESIGN		REFERENCE	NEXT	ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
ADDRESS					DRFT	CASTIGLIONE		DATE	MFG	DATE
					CHRD			DATE	APPR	DATE
							B. MIZE		MAY 29, 2018	
DIVISION				DIVISION CODE		 3M Center St. Paul, MN 55144 © 3M COPYRIGHT 2018 This document and the information it contains are 3M property and may not be reproduced or further distributed without the written permission of, or used or disclosed other than for 3M authorized purposes. All rights reserved.				
DO NOT SCALE DRAWING		SCALE		TOLERANCES EXCEPT AS NOTED		INCHES 0.0 0.00 0.000 0.000 ±				
		THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 2009		ROUND, SHIELDED / JACKETED, FLAT, CABLE, 0.050", HF659				
MAX SURFACE ROUGHNESS 0.0 0.00 0.00 ±		MAX SURFACES 0.0 0.00 0.00 ±		WILL METERS 0.0 0.00 0.00 ±		CAGE NUMBER SIZE DRAWING NO. REV.				
✓ MARKED ONLY		✓ MARKED ONLY		ANGLE		MODEL HF659 DEF. YES NO SHT 1 OF 2				

1. REGULATORY INFORMATION:
VISIT 3M.com/regs OR CONTACT
YOUR 3M REPRESENTATIVE TO FIND
THE RoHS COMPLIANCE STATUS OF
THE 3M PART YOU ARE INTERESTED
IN.

2. IN THE EVENT OF CONFLICT
BETWEEN THIS DATA AND THAT
CONTAINED IN THE PRODUCT
SPECIFICATION, THE PRODUCT
SPECIFICATION TAKES PRECEDENT.

REVISION

3

78-5100-2335-7
DRAWING NUMBER

--	--

1

1

[illegible]

1

1

A

[illegible]

1

[illegible]

