

MIRELLA-50-S-PIN

~15° spot beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 49.9 mm
Height	23.9 mm
Fastening	pin
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish	Coating
MIRELLA-50-S-PIN	Reflector	PC	metal		lacquer



ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12480_MIRELLA-50-S-PIN » Box size: 480 x 280 x 300 mm	336	112	28	3.0





PHOTOMETRIC DATA (MEASURED):





LED SM4
FWHM 15.0°
Efficiency 81 %
Peak intensity 6.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL




LED MHB-A/B
FWHM 16.0°
Efficiency 85 %
Peak intensity 7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



LED MHB-A/B
FWHM 17.0°
Efficiency 85 %
Peak intensity 5.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL




LED MHB-A/B
FWHM 14.0°
Efficiency 90 %
Peak intensity 9.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED XHP50
FWHM 16.0°
Efficiency 89 %
Peak intensity 5.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL




LED XHP50
FWHM 13.0°
Efficiency 93 %
Peak intensity 8.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XHP50
FWHM 22.0°
Efficiency 86 %
Peak intensity 2.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C13723_MIRELLA-RZL



LED XHP50
FWHM 14.0°
Efficiency 88 %
Peak intensity 7 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



PHOTOMETRIC DATA (MEASURED):



CREE

LED XM-L
FWHM 12.0°
Efficiency 86 %
Peak intensity 8.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



CREE

LED XM-L
FWHM 8.7°
Efficiency 90 %
Peak intensity 19.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE

LED XM-L
FWHM 12.0°
Efficiency 85 %
Peak intensity 11.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



CREE

LED XM-L RGB
FWHM 21.0°
Efficiency 84 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13723_MIRELLA-RZL



PHOTOMETRIC DATA (MEASURED):


CREE

LED XM-L2
FWHM 12.0°
Efficiency 86 %
Peak intensity 8.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL




CREE

LED XM-L2
FWHM 8.6°
Efficiency 91 %
Peak intensity 18.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



CREE

LED XP-G
FWHM 11.0°
Efficiency 86 %
Peak intensity 10.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



CREE

LED XP-G
FWHM 8.1°
Efficiency 91 %
Peak intensity 25 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):

CREE

LED XP-G
FWHM 11.0°
Efficiency 86 %
Peak intensity 14.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



CREE

LED XP-G2
FWHM 7.9°
Efficiency 91 %
Peak intensity 25.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





CREE

LED XP-G2
FWHM 11.0°
Efficiency 87 %
Peak intensity 10.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



CREE

LED XP-L HI
FWHM 7.7°
Efficiency 90 %
Peak intensity 24.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):

CREE

LED XT-E
FWHM 11.0°
Efficiency 85 %
Peak intensity 9.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



CREE

LED XT-E
FWHM 7.6°
Efficiency 89 %
Peak intensity 24 cd/lm
LEDs/each optic 1
Light colour White
Required components:





CREE

LED XT-E
FWHM 10.0°
Efficiency 84 %
Peak intensity 14.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



LUMILEDS

LED LUXEON 5050 Round LES
FWHM 11.0°
Efficiency 93 %
Peak intensity 11.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED LUXEON A
FWHM 12.0°
Efficiency 85 %
Peak intensity 8.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



LUMILEDS

LED LUXEON A
FWHM 8.9°
Efficiency 89 %
Peak intensity 20.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON A
FWHM 10.0°
Efficiency 85 %
Peak intensity 14.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



LUMILEDS


LED LUXEON C
FWHM 22.0°
Efficiency 81 %
Peak intensity 3.1 cd/lm
LEDs/each optic 4
Light colour RGBW
Required components:
C13723_MIRELLA-RZL





PHOTOMETRIC DATA (MEASURED):



LED LUXEON M/MX
FWHM 15.0°
Efficiency 86 %
Peak intensity 5.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL



LED LUXEON M/MX
FWHM 12.0°
Efficiency 91 %
Peak intensity 10.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON M/MX
FWHM 15.0°
Efficiency 85 %
Peak intensity 7.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL




LED LUXEON MZ
FWHM 11.0°
Efficiency 85 %
Peak intensity 9.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL





PHOTOMETRIC DATA (MEASURED):



LED LUXEON MZ
FWHM 8.7°
Efficiency 90 %
Peak intensity 19.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Z
FWHM 18.0°
Efficiency 82 %
Peak intensity 3.4 cd/lm
LEDs/each optic 4
Light colour RGBW
Required components:
C13723_MIRELLA-RZL



LED NS9x383
FWHM 12.0°
Efficiency 85 %
Peak intensity 8.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL





LED NS9x383
FWHM 9.2°
Efficiency 89 %
Peak intensity 17.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LED NV4x144A
 FWHM 13.0°
 Efficiency 92 %
 Peak intensity 9.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED Duris S8
 FWHM 11.0°
 Efficiency 86 %
 Peak intensity 11.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13333_MIRELLA-CL



LED Duris S8
 FWHM 12.0°
 Efficiency 86 %
 Peak intensity 8.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12479_MIRELLA-DL



LED Duris S8
 FWHM 9.7°
 Efficiency 91 %
 Peak intensity 16 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):

OSRAM Opto Semiconductors

LED OSLON Square EC
FWHM 11.0°
Efficiency 85 %
Peak intensity 9.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12479_MIRELLA-DL




OSRAM Opto Semiconductors

LED OSLON Square EC
FWHM 8.0°
Efficiency 90 %
Peak intensity 23.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM Opto Semiconductors

LED OSLON Square EC
FWHM 9.4°
Efficiency 85 %
Peak intensity 15.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



OSRAM Opto Semiconductors


LED Ostar-SMT RGB
FWHM 19.0°
Efficiency 85 %
Peak intensity 3.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13723_MIRELLA-RZL



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LH508A
FWHM 12.0°
Efficiency 90 %
Peak intensity 10.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SEOUL SEMICONDUCTOR

LED F50360 (RGB)
FWHM 21.0°
Efficiency 84 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13723_MIRELLA-RZL



SEOUL SEMICONDUCTOR


LED F50360 (RGB)
FWHM 19.0°
Efficiency 86 %
Peak intensity 3.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13723_MIRELLA-RZL




PHOTOMETRIC DATA (SIMULATED):





LED XHP35 HD
FWHM 11.0°
Efficiency 92 %
Peak intensity 11.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON 5258
FWHM 9.0°
Efficiency 91 %
Peak intensity 17 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED OSCONIQ P 7070
FWHM 11.0°
Efficiency 87 %
Peak intensity 10.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13333_MIRELLA-CL



LED OSCONIQ P 7070
FWHM 10.0°
Efficiency 92 %
Peak intensity 11.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)