





## Heyco® Rubber Push-In Bumpers

| Panel Dimensions   |     |                   |     | Part No. | Description | Material | Part Dimensions    |     |                  |     |                      |     |                    |     | Type |
|--------------------|-----|-------------------|-----|----------|-------------|----------|--------------------|-----|------------------|-----|----------------------|-----|--------------------|-----|------|
| Mounting Hole Dia. |     | Maximum Thickness |     |          |             |          | A<br>Base Diameter |     | B<br>Base Height |     | C<br>Insert Diameter |     | D<br>Insert Height |     |      |
| in.                | mm. | in.               | mm. |          |             |          | in.                | mm. | in.              | mm. | in.                  | mm. | in.                | mm. |      |



TYPE F1




TYPE F2

|      |      |     |     |              |                 |         |      |      |     |     |     |      |     |     |    |
|------|------|-----|-----|--------------|-----------------|---------|------|------|-----|-----|-----|------|-----|-----|----|
| .156 | 4,0  | .03 | 0,8 | <b>G2004</b> | RGB 156-375-3   | SBR     | .38  | 9,5  | .09 | 2,4 | .22 | 5,5  | .11 | 2,8 | F1 |
| .187 | 4,7  | .06 | 1,6 | <b>G2012</b> | RGB 187-375-4   | SBR     | .38  | 9,5  | .13 | 3,2 | .25 | 6,4  | .13 | 3,2 | F2 |
|      |      |     |     | <b>G2013</b> | RGB 187-500-3   | Nitrile | .50  | 12,7 | .09 | 2,4 | .25 | 6,4  | .19 | 4,7 | F2 |
| .250 | 6,4  | .05 | 1,3 | <b>G2021</b> | RGB 250-562-12  | SBR     | .56  | 14,3 | .38 | 9,5 | .34 | 8,6  | .27 | 6,7 | F2 |
|      |      |     |     | <b>G2022</b> | RGB 250-375-4   | SBR     | .38  | 9,5  | .13 | 3,2 | .31 | 7,9  | .06 | 1,6 |    |
|      |      |     |     | <b>G2023</b> | RGB 250-375-4R* | SBR     | .38  | 9,5  | .13 | 3,2 | .31 | 7,9  | .06 | 1,6 | F2 |
|      |      | .06 | 1,6 | <b>G2024</b> | RGB 250-500-5   | SBR     | .50  | 12,7 | .16 | 4,0 | .31 | 7,9  | .13 | 3,2 | F1 |
|      |      |     |     | <b>G2025</b> | RGB 250-500-8   | SBR     | .50  | 12,7 | .25 | 6,4 | .31 | 7,9  | .13 | 3,2 | F1 |
|      |      | .13 | 3,2 | <b>G2026</b> | RGB 250-406-7   | Nitrile | .41  | 10,3 | .22 | 5,5 | .34 | 8,7  | .06 | 1,6 | F2 |
| .281 | 7,1  |     |     | <b>G2027</b> | RGB 250-562-4   | SBR     | .56  | 14,3 | .13 | 3,2 | .34 | 8,7  | .13 | 3,2 | F1 |
|      |      | .05 | 1,2 | <b>G2029</b> | RGB 281-500-2   | Nitrile | .50  | 12,7 | .06 | 1,6 | .38 | 9,5  | .16 | 4,0 | F2 |
|      |      |     |     | <b>G2030</b> | RGB 281-500-4   | SBR     | .50  | 12,7 | .13 | 3,2 | .38 | 9,5  | .16 | 4,0 | F2 |
|      |      | .08 | 2,0 | <b>G2031</b> | RGB 281-562-4   | SBR     | .56  | 14,3 | .13 | 3,2 | .38 | 9,5  | .16 | 4,0 | F1 |
| .312 | 7,9  | .13 | 3,2 | <b>G2032</b> | RGB 281-625-11  | SBR     | .63  | 15,9 | .34 | 8,7 | .44 | 11,1 | .17 | 4,3 | F1 |
|      |      | .05 | 1,2 | <b>G2034</b> | RGB 312-1250-3  | SBR     | 1,25 | 28,6 | .09 | 2,4 | .44 | 11,1 | .08 | 2,0 | F2 |
|      |      | .08 | 2,0 | <b>G2036</b> | RGB 312-875-4   | SBR     | .88  | 22,2 | .13 | 3,2 | .50 | 12,7 | .06 | 1,6 |    |
| .500 | 12,7 | .19 | 4,8 | <b>G2044</b> | RGB 500-1000-10 | SBR     | 1,00 | 25,4 | .31 | 7,9 | .69 | 17,4 | .19 | 4,7 | F1 |

Standard color black.

\*Part number G2023 has a round insertion head.



TYPE F3

|      |     |     |     |              |                |     |     |      |     |     |     |     |     |     |    |
|------|-----|-----|-----|--------------|----------------|-----|-----|------|-----|-----|-----|-----|-----|-----|----|
| .180 | 4,6 | .11 | 2,8 | <b>G2007</b> | RGB 180-500-2  | SBR | .50 | 12,7 | .06 | 1,5 | .25 | 6,4 | .08 | 2,0 | F3 |
| .187 | 4,7 | .05 | 1,3 | <b>G2010</b> | RGB 187-312-4  | SBR | .31 | 7,9  | .13 | 3,2 | .25 | 6,4 | .09 | 2,4 |    |
|      |     | .05 | 1,3 | <b>G2011</b> | RGB 187-375-8  | SBR | .38 | 9,5  | .25 | 6,4 | .25 | 6,4 | .30 | 7,5 |    |
|      |     | .08 | 2,0 | <b>G2014</b> | RGB 187-338-6* | SBR | .34 | 8,6  | .17 | 4,4 | .25 | 6,4 | .30 | 7,5 |    |
| .250 | 6,4 | .05 | 1,2 | <b>G2019</b> | RGB 250-437-6  | SBR | .44 | 11,1 | .19 | 4,7 | .31 | 7,9 | .13 | 3,2 |    |
| .312 | 7,9 | .09 | 2,4 | <b>G2037</b> | RGB 312-625-8  | SBR | .63 | 15,9 | .25 | 6,4 | .38 | 9,5 |     |     |    |

Standard color black.

\*Part number G2014 has a hollow core head.



Quick  
Specs

Material SBR or Nitrile  
Temperature Range -40°F (-40°C) to 221°F (105°C)