

**Isolation Partitions**

Isolation partitions provide separation between terminal blocks with different potentials. When used for DC power applications, voltages of up to ± 600V DC can be used on either side of the isolation partition. They also provide visual separation between groups of blocks.

- Material: polyamide 6.6
- Standard color: gray

**PARTITIONS**



| Cat. No.  | Std. Pk. | Dimensions (H x L x W) | Suitable for:               |
|-----------|----------|------------------------|-----------------------------|
| PP2.5/4UN | 50       | 37 x 44 x 1.6          | CTS2.5UN/4UN/CTT2.5UK/T/J/E |
| PP6/10U   | 50       | 37.5 x 56.5 x 1.5      | CTS6U/CTS10U                |
| PP25U     | 50       | 46.5 x 62 x 1.5        | CTS25U                      |
| PP25UN    | 50       | 42.5 x 62 x 1          | CTS25UN                     |
| PP35U     | 50       | 50 x 64.5 x 1.5        | CTS35U                      |
| PP35UN    | 50       | 50 x 64.5 x 1          | CTS35UN                     |
| PPCMT4    | 50       | 32.5 x 37 x 1.6        | CMT4/CMT4S/CMT4SU           |
| PPCSFL4U  | 50       | 42.5 x 62 x 1.5        | CSFL4U/4U(L)/CSDL4U         |
| PPCSC2.5T | 50       | 28 x 58.7 x 1.5        | CSC2.5T/CSCG2.5T            |
| PPCSC4T   | 50       | 33 x 65 x 1.5          | CSC4T/CSCG4T                |
| PPCSC6T   | 50       | 36.5 x 72 x 2          | CSC6T/CSCG6T                |

**Separator Plates**

Used for electrical separation of adjacent jumpers. They can be inserted after the terminal blocks have been assembled on DIN rail. There is no loss of width.


**SEPARATOR PLATES**



| Cat. No.  | Std. Pk. | Dimensions (H x L x W) | Suitable for:                     |
|-----------|----------|------------------------|-----------------------------------|
| SP2.5/4UN | 100      | 17.5 x 17.4 x 1.4      | CTS2.5UN/4UN/CTT2.5UK/T/J/E       |
| SP6/10U   | 100      | 15.4 x 16.2 x 1.5      | CTS6U/CTS10U/16U                  |
| SPCDL4U   | 100      | 15.4 x 16.2 x 1.6      | CDL4U/CDL4U(I.S)/ CDL4U(E) Series |
| SPCMB4    | 100      | 14.5 x 12 x 1.5        | CMB4                              |
| SPCDLG2.5 | 100      | 11 x 10.5 x 1          | CDLG2.5                           |


**Protective Cover / Side Holding Plates**

For protection against dust and shock, transparent protective cover can be installed above the terminal block assembly with the aid of side/holding plates. The side holding plates can be fitted on 35 mm and 32 mm Din rails. These plates should be backed by standard end stops.



*Assembled Block installed with Protective Cover*

**CTSPC**



*For all Rail Mounting Terminals  
\*Other lengths available on request.*

**CSP1**



*Mounting Accessories for CTSPC*