

9808	9101	5650	8679
9808-0-15-XX-16-XX-04-0 Press-fit in 1,70 mounting hole	9101-0-15-XX-16-XX-10-0 Press-fit in 1,70 mounting hole	5650-0-19-XX-16-XX-10-0 Press-fit in 1,70 mounting hole	8679-0-15-XX-16-XX-10-0 Solder mount in 1,80 min. mounting hole

8827	6021	1873
8827-0-15-XX-16-XX-04-0 Press-fit in 1,55 mounting hole	6021-0-15-XX-16-XX-10-0 Solder mount in 1,57 min. mounting hole	1873-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole

--	--	--	--

SPECIFICATIONS SHELL MATERIAL: Brass Alloy 360, 1/2 Hard CONTACT MATERIAL: Beryllium Copper Alloy 172, HT DIMENSION IN INCHES TOLERANCES ON: LENGTHS: $\pm 0,13$ DIAMETERS: $\pm 0,05$ ANGLES: $\pm 2^\circ$	ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0 BASIC PART # _____ SPECIFY SHELL FINISH: _____ 01 5,08μm TIN/LEAD OVER NICKEL ◇ 80 5,08μm TIN OVER NICKEL (RoHS) ◇ 15 0,25μm GOLD OVER NICKEL (RoHS) SPECIFY CONTACT FINISH: _____ 01 5,08μm TIN/LEAD OVER NICKEL ◇ 80 5,08μm TIN OVER NICKEL (RoHS) ◇ 27 0,76μm GOLD OVER NICKEL (RoHS) CONTACT #16 CONTACT (DATA ON PAGE 222)
--	---