

9808	9101	5650	8679
<p>9808-0-15-XX-16-XX-04-0 Press-fit in 1,70 mounting hole</p>	<p>9101-0-15-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>5650-0-19-XX-16-XX-10-0 Press-fit in 1,70 mounting hole</p>	<p>8679-0-15-XX-16-XX-10-0 Solder mount in 1,80 min. mounting hole</p>

8827	6021	1873
<p>8827-0-15-XX-16-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p>6021-0-15-XX-16-XX-10-0 Solder mount in 1,57 min. mounting hole</p>	<p>1873-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole</p>

--	--	--	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µmTIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)</p> <p>SPECIFY CONTACT FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)</p> <p style="text-align: center;">CONTACT #16 CONTACT (DATA ON PAGE 222)</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> <p>RoHS 2002/95/EC</p> </div>
--	---