

REV.	DESCRIPTION	DATE	APPROVED
A	Engineering Release	10/21/13	G. W.



NOTES:


- 2. DIRECT REPLACEMENT FOR T1 3/4 MIDGET FLANGE SX6s BASED LAMPS
- 1. CENTER CONTACT ANODE

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		BIVAR [®] 4 THOMAS, IRVINE, CA. 92618																	
<u>DECIMALS</u>	<u>ANGULAR</u>																		
.X ± .1	X° ± 1°	<table border="1" style="width: 100%;"> <tr> <td>DESIGNED:</td> <td>DATE:</td> <td rowspan="2">TITLE: 206 SERIES INCANDESCENT REPLACEMENT LED</td> <td>REVISION:</td> </tr> <tr> <td>Alex Wright</td> <td>10/21/13</td> <td>PART NO: LFR-206X-XXX</td> <td>A</td> </tr> <tr> <td>CHECKED:</td> <td>DATE:</td> <td>CAGE CODE : 32559</td> <td>SHEET # 1 OF 2</td> </tr> <tr> <td>Minh Doan</td> <td>10/21/13</td> <td colspan="2">CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.</td> </tr> </table>		DESIGNED:	DATE:	TITLE: 206 SERIES INCANDESCENT REPLACEMENT LED	REVISION:	Alex Wright	10/21/13	PART NO: LFR-206X-XXX	A	CHECKED:	DATE:	CAGE CODE : 32559	SHEET # 1 OF 2	Minh Doan	10/21/13	CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.	
DESIGNED:	DATE:			TITLE: 206 SERIES INCANDESCENT REPLACEMENT LED	REVISION:														
Alex Wright	10/21/13				PART NO: LFR-206X-XXX	A													
CHECKED:	DATE:	CAGE CODE : 32559	SHEET # 1 OF 2																
Minh Doan	10/21/13	CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.																	
.XX ± .02																			
.XXX ± .010																			


REV.	DESCRIPTION	DATE	APPROVED
	SEE SHEET #1		

DERATING CURVES


Derating Graph 1




Derating Graph 2



Derating Graph 3





Derating Graph 4



Bivar Part Number	Wave Length λp(nm)	Emitted Color	Lens Appearance	Operating Voltage	Electro-Optical Data		Viewing Angle	De-rating Graphs
				Vopr (Vdc)	Current DC (mA)	Iv (mcd)		
				TYP	TYP	TYP		
LFR-206R12V	630	RED	CLEAR	12	10	600	120	1
LFR-206R28V	630	RED	CLEAR	28	8	600	120	1
LFR-206Y12V	585	YELLOW	CLEAR	12	10	600	120	1
LFR-206Y28V	585	YELLOW	CLEAR	28	8	600	120	1
LFR-206G12V	515	GREEN	CLEAR	12	10	800	120	2
LFR-206G28V	515	GREEN	CLEAR	28	8	800	120	2
LFR-206B12V	465	BLUE	CLEAR	12	10	230	120	4
LFR-206B28V	465	BLUE	CLEAR	28	8	230	120	4
Bivar Part Number	Chromaticity Coordinates	Emitted Color	Lens Appearance	Operating Voltage	Electro-Optical Data		Viewing Angle	De-rating Graphs
				Vopr (Vdc)	Current DC (mA)	Iv (mcd)		
				TYP	TYP	TYP		
LFR-206WW12V	X=0.4255~0.4680 Y=0.4000~0.4385	WARM WHITE	CLEAR	12	10	850	120	3
LFR-206WW28V	X=0.4255~0.4680 Y=0.4000~0.4385	WARM WHITE	CLEAR	28	8	850	120	3
LFR-206CW12V	X=0.31 Y=0.32	COOL WHITE	CLEAR	12	10	1100	120	3
LFR-206CW28V	X=0.31 Y=0.32	COOL WHITE	CLEAR	28	8	1100	120	3

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

MAXIMUM POWER DISSIPATION _____ 500 mW
 OPERATING TEMPERATURE RANGE _____ -40°C ~ 85°C
 STORAGE TEMPERATURE _____ -40°C ~ 100°C

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED) DECIMALS ANGULAR		 BIVAR [®] 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
			
DESIGNED: Alex Wright	DATE: 10/21/13	TITLE: 206 SERIES INCANDESCENT REPLACEMENT LED	
CHECKED: Minh Doan	DATE: 10/21/13	PART NO: LFR-206X-XXX	REVISION: A
		CAGE CODE : 32559	SHEET # 2 OF 2
CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.			