

## For Patient-Care Vicinity: UL 60601-1 Medical-Grade Power Strip w/Surge Protection, 4 Hospital-Grade Outlets, 6 ft. Cord

MODEL NUMBER: **SPS406HGULTRA**



### Highlights

- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- 4 NEMA 5-15R-HG hospital-grade outlets with locking safety covers
- Automatic single-fault detection for added patient protection

### Package Includes

- SPS406HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner's manual

### Description

The SPS406HGULTRA Medical-Grade Power Strip -- patent #7,375,939 and 8,339,759 -- is designed and listed to full 60601-1 and 60950-1 compliance, making it ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas.

This 120V, 60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets that include integrated locking safety covers. Plus, 1410 joules of surge suppression prevent dangerous power spikes that can damage connected equipment and destroy data. A 15A resettable circuit breaker also protects your equipment from overloads. An LED indicator tells you power is present and protected from surges (with no ground faults or line/neutral reversals).

Mounting slots and flanges let you install the SPS406HGULTRA on a wide variety of surfaces. The all-metal housing ensures safety and is guaranteed to stand up to demanding environments.

With a switchless design that prevents accidental shutoff and a six-foot power cord that provides flexibility in placing the power strip, the SPS406HGULTRA is a recommended replacement for all non-compliant power strips.

### Features

#### Power Distribution Anywhere in Any Medical Facility

- Ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas
- 120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specifications
- Automatic single-fault protection
- Tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standards
- Patent # 7,375,939 & 8,339,759

#### Versatile Medical-Grade Solution

- 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power



- 6 ft. power cord with NEMA 5-15P-HG plug provides ample reach to the power source
- Rugged all-metal housing for long life in demanding environments

#### Premium Safety Features

- 1410 joules of surge suppression protect against dangerous power spikes
- Integrated locking outlet safety covers block access to unused outlets
- Built-in 15A resettable circuit breaker protects against dangerous overloads
- Switchless design prevents accidental shut-off
- LED indicates power is present and surge-protected

#### Ready to Use Right Out of the Box

- Built-in mounting slots and flanges for easy installation on a variety of surfaces

## Specifications

OUTPUT	
Frequency Compatibility	60 Hz
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15
Overload Protection	15A resettable circuit breaker
Outlet Safety Covers	Yes
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Input Connection Type	NEMA 5-15P-HG
Input Cord Length (ft.)	6
Input Cord Length (m)	1.83
Voltage Compatibility (VAC)	120
Maximum Surge Amps	60000
Right-Angle Plug	No
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Proper wiring and surge protection working
SURGE / NOISE SUPPRESSION	



AC Suppression Joule Rating	1410
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4
Unit Weight (lbs.)	3.2
Unit Weight (kg)	1.45
Material of Construction	Metal
Integrated Keyhole Mounting Tabs	Yes
Receptacle Color	White
Color (AC Line Cord)	White
<b>CERTIFICATIONS</b>	
Approvals	TUV tested and Listed to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada)
Patented	Patent# 7,375,939; Patent# 8,339,759
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>