


This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.



Customer drawing

DIM.S SHELL	A	B	C	D	Pitch
15	30.84	16.92	24.99	19.28	2.29
26	39.24	24.70	33.32	27.51	2.29
44	53.04	38.96	47.04	41.30	2.29
62	69.32	55.42	63.50	57.71	2.41

REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
1			10/10/08	

D-SUB TECHNICAL DATA

SHELL : Steel 2.5um (100u") min tin over 1.25um (50u") min nickel
BODY : Glass filled thermoplastic.
Flame retardant to UL94 V-0 Color Black
CONTACTS : Brass
15u"min gold over 50u" min nickel on mating area
100u" min tin over 50u" min nickel on solder area
SCREWLOCK : Brass, 50u" min nickel
ELECTRICAL : Voltage rating : 1000 V RMS at 50 Hz
Current rating 3A.
Insulation resistance >1000 M Ohms
Contact resistance 20 mOhms max.
CLIMATIC : Temperature range -55 °C up to 125°C
MARKING : Amphenol—...(Series No.)
Commercial reference
Manufacturing date

PRODUCT CODE

L 777 HD X XX P VF

L:RoHS Compliance

777: tinned shell +
dimples for plug


HD: High density

Shell Size	:E,A,B,C
------------	----------

Front mounting type:
VFM=front
screwlock 4-40

Contact type:
P: Male

Configuration: 15,26,44,62

UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE		Amphenol[®]			
TOLERANCES		DRAWN		Christine.cui				10/10/08	
U.S.		CHECKED		lik.wang				10/10/08	
METRIC		CHECKED							
.X +/- 0.50									
.XX +/- 0.30									
.XXX +/- 0.20									
FRACTIONS +/-									
ANGLES +/- 2°									
FOR MATERIALS AND FINISHES SEE NOTES		DRAWING FILE :		TITLE					
REMOVE SHARP EDGES				stamped and formed connector, HD series					
DIMENSIONS		ANGLE OF PROJECTION							
				SIZE		DRAWING NO.			
U.S.				A4		C L777HDXXPVF			
INCHES						REV.			
METRIC						1			
MM				SCALE		NONE			
				SHEET		1 OF 1			