

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
	G	Contact pin base material change from CuSn (Phosphor bronze) to CuZn (Brass). Plating change from min. 0.8microns gold plating to min. 0.7µm Pd Ni + 0.1µm gold flash at contact area (Area F).		24JUN2014	TJ	JK	


NUMMER 825440	
VERWENDET FÜR E 92-9802	
WAR NR. —	

POLZ. PRO REIHE	L±0.5	BESTELL-NR.
—	—	—
2	5.08	825 440 -2
3	7.62	-3
4	10.16	-4
5	12.70	-5
6	15.24	-6
7	17.78	-7
8	20.32	-8
9	22.86	-9
10	25.40	1-
11	27.94	1-
12	30.48	1-
13	33.02	1-
14	35.56	1-
15	38.10	1-
16	40.64	1-
17	43.18	1-
18	45.72	1-
19	48.26	1-
20	50.80	2-
21	53.34	2-
22	55.88	2-
23	58.42	2-
24	60.96	2-
25	63.50	2-
26	66.04	2-
27	68.58	2-
28	71.12	2-
29	73.66	2-
30	76.20	3-
31	78.74	3-
32	81.28	3-
33	83.82	3-
34	86.36	3-
35	88.90	3-
36	91.44	3-
37	93.98	3-
38	96.52	3-
39	99.06	3-
40	101.60	4-
41	104.14	4-
42	106.68	4-
43	109.22	4-
44	111.76	4-
45	114.30	4-
46	116.84	4-
47	119.38	4-
48	121.92	4-
49	124.46	4-
50	127.00	5- 825 440 -0

STECKSEITE: IM BEREICH "F" MIN 0.7µmPdNi+0.1µm GOLD FLASH ÜBER 1.27 µm NICKEL.
LÖTSEITE: MIN. 2.5 µm ZINN ÜBER 1.27 µm NICKEL

KONTAKTSTIFT	Cu Zn	⚠
STIFTGEHÄUSE	PBT GV	GRÜN
BENENNUNG	WERKSTOFF	OBERFLÄCHE FARBE

ZEICHNUNG GÜLTIG AB KW 39/96					
DIMENSIONS: mm	DWN 22.06.84 M.SCHAARSCHMIDT	MATERIAL —	FINISH —		
TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2 mm	CHK —	TE Connectivity			
0 PLC ± —	APVD —				
1 PLC ± —	PRODUCT SPEC 108-18012	NAME AMPMODU II PIN HEADER, DUAL ROW			
2 PLC ± —	APPLICATION SPEC —				
3 PLC ± —	WEIGHT —	SIZE A4	CAGE CODE 00779	DRAWING NO C-825440	RESTRICTED TO —
4 PLC ± —	CUSTOMER DRAWING				
ANGLES ± —	SCALE 4:1 SHEET 1 OF 2 REV G				

LOC —		DIST —		REVISIONS																																																																																																																																																																																																																							
		P	LTR	DESCRIPTION			DATE	DWN	APVD																																																																																																																																																																																																																		
			—	SEE SHEET 1			—	—	—																																																																																																																																																																																																																		
VERWENDET FÜR E 92-9802				CAD-ORIGINAL ZEICHNUNG NICHT ÄNDERN																																																																																																																																																																																																																							
WAR NR. —																																																																																																																																																																																																																											
<table><tr><td>Polz. pro Reihe</td><td>L±0.5</td><td colspan="2">Bestell-Nr.</td><td colspan="6">Bemerkung</td></tr><tr><td>1</td><td>2.54</td><td>5-</td><td>-1</td><td colspan="6"></td></tr><tr><td>2</td><td>5.08</td><td>5-</td><td>-2</td><td colspan="6"></td></tr><tr><td>3</td><td>7.62</td><td>5-</td><td>-3</td><td colspan="6"></td></tr><tr><td>4</td><td>10.16</td><td>5-</td><td>-4</td><td colspan="6"></td></tr><tr><td>5</td><td>12.70</td><td>5-</td><td>-5</td><td colspan="6"></td></tr><tr><td>6</td><td>15.24</td><td>5-</td><td>-6</td><td colspan="6"></td></tr><tr><td>7</td><td>17.78</td><td>5-</td><td>-7</td><td colspan="6"></td></tr><tr><td>8</td><td>20.32</td><td>5-</td><td>-8</td><td colspan="6"></td></tr><tr><td>9</td><td>22.86</td><td>5-</td><td>-9</td><td colspan="6"></td></tr><tr><td>10</td><td>25.40</td><td>6-</td><td>0</td><td colspan="6"></td></tr><tr><td>11</td><td>27.94</td><td>6-</td><td>-1</td><td colspan="6"></td></tr><tr><td>12</td><td>30.48</td><td>6-</td><td>-2</td><td colspan="6"></td></tr><tr><td>13</td><td>33.02</td><td>6-</td><td>-3</td><td colspan="6"></td></tr><tr><td>14</td><td>35.56</td><td>6-</td><td>-4</td><td colspan="6"></td></tr><tr><td>15</td><td>38.10</td><td>6-</td><td>-5</td><td colspan="6"></td></tr><tr><td>16</td><td>40.64</td><td>6-</td><td>-6</td><td colspan="6"></td></tr><tr><td>17</td><td>43.18</td><td>6-</td><td>825 440 -7</td><td colspan="6">△</td></tr><tr><td>18</td><td>45.72</td><td>6-</td><td>-8</td><td colspan="6"></td></tr><tr><td>19</td><td>48.26</td><td>6-</td><td>-9</td><td colspan="6"></td></tr><tr><td>20</td><td>50.80</td><td>7-</td><td>0</td><td colspan="6"></td></tr></table>										Polz. pro Reihe	L±0.5	Bestell-Nr.		Bemerkung						1	2.54	5-	-1							2	5.08	5-	-2							3	7.62	5-	-3							4	10.16	5-	-4							5	12.70	5-	-5							6	15.24	5-	-6							7	17.78	5-	-7							8	20.32	5-	-8							9	22.86	5-	-9							10	25.40	6-	0							11	27.94	6-	-1							12	30.48	6-	-2							13	33.02	6-	-3							14	35.56	6-	-4							15	38.10	6-	-5							16	40.64	6-	-6							17	43.18	6-	825 440 -7	△						18	45.72	6-	-8							19	48.26	6-	-9							20	50.80	7-	0						
Polz. pro Reihe	L±0.5	Bestell-Nr.		Bemerkung																																																																																																																																																																																																																							
1	2.54	5-	-1																																																																																																																																																																																																																								
2	5.08	5-	-2																																																																																																																																																																																																																								
3	7.62	5-	-3																																																																																																																																																																																																																								
4	10.16	5-	-4																																																																																																																																																																																																																								
5	12.70	5-	-5																																																																																																																																																																																																																								
6	15.24	5-	-6																																																																																																																																																																																																																								
7	17.78	5-	-7																																																																																																																																																																																																																								
8	20.32	5-	-8																																																																																																																																																																																																																								
9	22.86	5-	-9																																																																																																																																																																																																																								
10	25.40	6-	0																																																																																																																																																																																																																								
11	27.94	6-	-1																																																																																																																																																																																																																								
12	30.48	6-	-2																																																																																																																																																																																																																								
13	33.02	6-	-3																																																																																																																																																																																																																								
14	35.56	6-	-4																																																																																																																																																																																																																								
15	38.10	6-	-5																																																																																																																																																																																																																								
16	40.64	6-	-6																																																																																																																																																																																																																								
17	43.18	6-	825 440 -7	△																																																																																																																																																																																																																							
18	45.72	6-	-8																																																																																																																																																																																																																								
19	48.26	6-	-9																																																																																																																																																																																																																								
20	50.80	7-	0																																																																																																																																																																																																																								
△ VERPACKUNG:25 STÜCK IN PLASTIK-DOSE PN 165 439-1 MIT PLASTIK-DECKEL PN 165 440-1																																																																																																																																																																																																																											
△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI																																																																																																																																																																																																																											
△ OBSOLETE																																																																																																																																																																																																																											
<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">BENENNUNG</td><td colspan="2">WERKSTOFF</td><td colspan="2">OBERFLÄCHE</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">FARBE</td></tr></table>																						BENENNUNG		WERKSTOFF		OBERFLÄCHE						FARBE																																																																																																																																																																																											
BENENNUNG		WERKSTOFF		OBERFLÄCHE																																																																																																																																																																																																																							
				FARBE																																																																																																																																																																																																																							
ZEICHNUNG GÜLTIG AB KW 39./96																																																																																																																																																																																																																											
DIMENSIONS: mm		DWN A.HO 07.06.84		MATERIAL —		FINISH —																																																																																																																																																																																																																					
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± — 4 PLC ± — ANGLES ± —		CHK M.SCHAARSCHMIDT 13.06.84		 TE Connectivity																																																																																																																																																																																																																							
		APVD —																																																																																																																																																																																																																									
		PRODUCT SPEC —		NAME AMPMODU II STIFTLEISTE ZWEIREIHIG																																																																																																																																																																																																																							
		APPLICATION SPEC —																																																																																																																																																																																																																									
		WEIGHT —		SIZE A4		CAGE CODE 00779		DRAWING NO C-825440		RESTRICTED TO —																																																																																																																																																																																																																	
		CUSTOMER DRAWING																																																																																																																																																																																																																									
		SCALE 4:1		SHEET 2 OF 2		REV G																																																																																																																																																																																																																					