



Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessory
Product specific application	Heavy hoisting applications
Product compatibility	XKM
Accessory / separate part type	Contact block
Number of contacts	4
Contact blow-out type	Magnetic

Complementary

Electrical connection	Screw clamp terminal, connection capacity: 1 x 1.5...2 x 2.5 mm ²
Contact operation	Double-break Slow-break
[Ith] conventional free air thermal current	20 A conforming to IEC 337-1 20 A conforming to NF C 63-140 20 A conforming to VDE 0660
[Ui] rated insulation voltage	500 V AC/DC conforming to IEC 158-1 500 V AC/DC conforming to NF C 20-040 500 V AC/DC conforming to VDE 0110 600 V conforming to CSA C22.2 No 14
Positive opening	With
Resistance across terminals	<= 25 MOhm at 1 A conforming to NF C 93-050
Short-circuit protection	20 A cartridge fuse type gG conforming to IEC 337-1B 20 A cartridge fuse type gG conforming to VDE 0660 part 2
Electrical durability	3000000 cycles DC inductive load at 120 V, power broken = 100 conforming to IEC 337-1 DC-11, operating rate = 60 cyc/mn 0.5 3000000 cycles DC inductive load at 24 V, power broken = 90 conforming to IEC 337-1 DC-11, operating rate = 60 cyc/mn 0.5 3000000 cycles DC inductive load at 48 V, power broken = 100 conforming to IEC 337-1 DC-11, operating rate = 60 cyc/mn 0.5
Product weight	0.74 lb(US) (0.335 kg)

Environment

standards	CENELEC EN 50013
-----------	------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------