

08080700 & 08080900 BATTERY DISCONNECT SWITCHES

300A • SPST • IP54 • M10 Studs

08080700 08080900



Description

Rotating Battery Switches and Selectors are ideal for vehicle and marine protection. The contacts are protected against accidental short-circuit by a housing with a removable lower cover and pre-cut sides to allow cable exit in the desired position.

Features/Benefits

- 300A continuous current rating
- M10 contacts in silver-plated copper
- Panel mount with 52mm key/handle exit hole.
- Waterproof to IP54

Mounting Diagram

Specifications

Max Operating Voltage:24V DCMax Continuous Current:300A

Ingress Protection: IP54

Contacts: Silver-plated Copper
Terminals: M10 (brass nuts)

Applications

Marine
 Off-Road


Agricultural
 Emergency Vehicles


Web Resources


Download 2D print and technical resources at: **littelfuse.com/ManualBatterySwitches**

Electrical Diagram

08080700 08080800 08080900







Ordering Information


PART NUMBER	VOLTAGE	AMPERAGE	POSITIONS	CIRCUITRY	MOUNTING	INGRESS	TERMINAL NUTS	NOTES
BOXED								
08080700	12-24V DC	300A	Knob: ON - OFF	SPST	Panel Mount	IP54	M10 Brass	Fixed knob
08080800	12-24V DC	300A	Key: ON - OFF	SPST	Panel Mount	IP54	M10 Brass	Removable key
08080900	12-24V DC	300A	Knob:1/2/1+2/0FF	SPST	Panel Mount	IP54	M10 Brass	Fixed knob (battery selector)


1 of 2





08080700 & 08080900 BATTERY DISCONNECT SWITCHES


Dimensions in millimeters
















Visit **Littelfuse.com** for the most up-to-date product information. Littelfuse reserves the right to make product changes, without notice. Material in this document is as accurate as known at the time of publication.