




### SMA Male Plug to SMM Male Plug

**Model Number****ADT-2848-SM-MMM-02****SPECIFICATIONS****Frequency:** DC - 18.0 GHz**VSWR:**  $1.04 + .007 f$  (GHz)**Impedance:** 50 Ohms**Finish:** Passivated Stainless Steel

### SMA Male Plug to SMM Female Jack

**Model Number****ADT-2846-SM-MMF-02****SPECIFICATIONS****Frequency:** DC - 18.0 GHz**VSWR:**  $1.04 + .007 f$  (GHz)**Impedance:** 50 Ohms**Finish:** Passivated Stainless Steel

### SMA Female Jack to SMM Female Jack

**Model Number****ADT-2845-SF-MMF-02****SPECIFICATIONS****Frequency:** DC - 18.0 GHz**VSWR:**  $1.04 + .007 f$  (GHz)**Impedance:** 50 Ohms**Finish:** Passivated Stainless Steel

### SMA Female Jack to SMM Male Plug

**Model Number****ADT-2847-SF-MMM-02****SPECIFICATIONS****Frequency:** DC - 10.0 GHz**VSWR:**  $1.04 + .007 f$  (GHz)**Impedance:** 50 Ohms**Finish:** Passivated Stainless Steel