

Stacking Height Guide for Parallel Board-to-Board Applications


Stacking Height Guide for Parallel Board-to-Board Applications (Continued)

Stacking Height mm inch		Connector Description	Pitch	Connector Sizes (No. of Positions)																Connector Sizes (No. of Positions) <i>Continued</i>																			
				10	12	14	16	20	22	24	30	34	38	40	46	50	54	56	60	64	70	76	80	84	100	114	120	140	152	160	180	190	200	220	228	240	266	280	320
1.00	0.039	.4mm Fine Stack	.4mm																																				
1.50	0.059	.4mm Fine Stack	.4mm																																				
1.50	0.059	.5mm Fine Stack	.5mm																																				
3.00	0.118	.8mm Fine Stack	.8mm																																				
3.90	0.154	.8mm Fine Stack	.8mm																																				
4.00	0.157	.5mm Fine Mate	.5mm																																				
4.00	0.157	.6mm Free Height	.6mm																																				
4.00	0.157	.8mm Fine Mate	.8mm																																				
4.20	0.165	.8mm Fine Stack	.8mm																																				
4.50	0.177	.5mm Fine Mate	.5mm																																				
4.50	0.177	.8mm Fine Mate	.8mm																																				
4.70	0.185	.8mm Fine Stack	.8mm																																				
5.00	0.197	.5mm Free Height	.5mm																																				
5.00	0.197	.6mm Free Height	.6mm																																				
5.00	0.197	.8mm Fine Stack	.8mm																																				
5.00	0.197	.8mm Free Height	.8mm																																				
5.50	0.217	.5mm Fine Mate	.5mm																																				
5.90	0.232	.8mm Fine Stack	.8mm																																				
6.00	0.236	.5mm Fine Mate	.5mm																																				
6.00	0.236	.5mm Free Height	.5mm																																				
6.00	0.236	.6mm Free Height	.6mm																																				
6.00	0.236	.8mm Free Height	.8mm																																				
6.35	0.250	AMPMODU 50/50	.050"																																				
6.60	0.260	MICTOR	.025"																																				
7.00	0.276	.5mm Free Height	.5mm																																				
7.00	0.276	.6mm Free Height	.6mm																																				
7.00	0.276	.8mm Fine Stack	.8mm																																				
7.00	0.276	.8mm Free Height	.8mm																																				
8.00	0.315	.5mm Free Height	.5mm																																				
8.00	0.315	.6mm Free Height	.6mm																																				
8.00	0.315	.8mm Free Height	.8mm																																				
8.00	0.315	1mm Free Height	1mm																																				
8.13	0.320	AMPMODU 50/50	.050"																																				
9.00	0.354	.5mm Free Height	.5mm																																				
9.00	0.354	.8mm Fine Stack	.8mm																																				
9.00	0.354	.8mm Free Height	.8mm																																				
9.00	0.354	1mm Free Height	1mm																																				
9.00	0.354	MICTOR	.025"																																				
9.91	0.390	AMPMODU 50/50	.050"																																				
10.00	0.394	.6mm Free Height	.6mm																																				
10.00	0.394	.8mm Free Height	.8mm																																				
10.00	0.394	1mm Free Height	1mm																																				
10.92	0.430	MICTOR	.025"																																				
11.00	0.433	.5mm Free Height	.5mm																																				
11.00	0.433	.6mm Free Height	.6mm																																				
11.00	0.433	.8mm Free Height	.8mm																																				
11.00	0.433	1mm Free Height	1mm																																				
12.00	0.472	.5mm Free Height	.5mm																																				
12.00	0.472	.6mm Free Height	.6mm																																				
12.00	0.472	.8mm Free Height	.8mm																																				
12.00	0.472	1mm Free Height	1mm																																				
12.57	0.495	MICTOR	.025"																																				
13.00	0.512	.6mm Free Height	.6mm																																				
13.00	0.512	.8mm Free Height	.8mm																																				
13.00	0.512	1mm Free Height	1mm																																				
13.08	0.515	AMPMODU System 50	.050"																																				
14.00	0.551	.6mm Free Height	.6mm																																				
14.00	0.551	.8mm Free Height	.8mm																																				
14.00	0.551	1mm Free Height	1mm																																				
15.00	0.591	.5mm Free Height	.5mm																																				
15.00	0.591	.6mm Free Height	.6mm																																				
15.00	0.591	.8mm Free Height	.8mm																																				
15.00	0.591	1mm Free Height	1mm																																				
15.61	0.615	MICTOR	.025"																																				
16.00	0.630	.5mm Free Height	.5mm																																				
16.00	0.630	.6mm Free Height	.6mm																																				

0.5mm Free Height (FH) Connectors

Product Facts

- Available position sizes:
 - For single connector: 120, 160, 200, 220, and 240 positions
 - For bridged connectors: 240, 320, and 440 positions
- Available stacking heights:
 - 5mm, 6mm, 7mm, 8mm, 9mm, 11mm, 12mm, 15mm, and 16mm (limited by position sizes)
- Giga ground shielding options on all parts
- RoHS Compliant part numbers available
- Polarized locating posts



0.5mm Free Height is a two-piece connector system designed for parallel board-to-board stacking applications. The contact system is identical to our popular 0.6mm FH product. The 0.5mm FH product has been chosen by the PICMG COM Express working group as the interface between embedded modules and carrier cards.

Applications

Parallel board-to-board for stacking applications that require high density. **The .5mm FH product is specified by the PICMG COM Express standard as the module to carrier card interface.** All stacking applications including Computer, Telecommunications, and Industrial industries.

Mechanical Properties

Operating Temperature — -40°C to +85°C
Durability — 30 cycles
Current Rating — 0.5A
Voltage Rating — 50 VAC
Dielectric Withstanding Voltage — 200 VAC

Technical Documents

Product Specification

108-5560


Test Reports

501-5226


0.5mm Free Height (FH) Connectors (Continued)

**Board Stacking Spacing by
Combined Receptacle and
Plug Assemblies**


5mm Height




6mm Height




7mm Height




8mm Height




11mm Height



12mm Height



16mm Height



0.5mm Free Height (FH) Connectors (Continued)

0.5 FH Height Lists

RECEPTACLE										PLUG	Remarks	Saleable Part No.	Packaging	SIF-200	G-Plate	Type	H	Pos.	200	220	240	240	440	240	240	120	200	120	160	200	220	320	440								
Remarks	Saleable Part No.	Packaging	SIF-200	G-Con	Type	H	Pos.	200	220		240	240	440	240	240	120	200	120	160	200	220	320	440	Pos.	200	220	240	240	440	240	240	120	200	120	160	200	220	320	440		
with Cap	2-6473527-9	Emboss	—	—	S	4	120									7H		8H																							
with Cap	3-6565778-5	Semi H/T	—	—	S	4	200	5H									7H			8H																					
with Cap	6-5353606-6	Hard Tray	—	X	S	4	220		5H												8H																				
	3-6318490-6	Hard Tray	—	X	S	4	220		5H												8H																				
with Cap	3-6473884-7	Hard Tray	—	—	S	4	240								6H	6H																									
with Cap	3-5353606-7	Hard Tray	—	X	S	4	240								6H	6H																									
with Cap	3-1827231-6	Hard Tray	—	X	B	4	440					5H																												8H	
with Cap	5-6123675-9	Emboss	—	X	B	4	240			5H	5H																														
	6-5353699-5	Hard Tray	—	X	S	8	200	9H									11H			12H																					
with Cap	6-5353700-5	Hard Tray	X	X	S	8	200										11H			12H																					
with Cap	6376618-1	Hard Tray	—	X	S	12	120								15H		16H																								
with Cap	6-5353703-2	Tray	X	X	S	12	160											16H																							
	6-5353649-2	Hard Tray	—	X	B	12	320																																	16H	

0.5mm Free Height (FH) Connectors (Continued)


Receptacle Assembly

Acceptable Board Stacking Height = 11mm/12mm

Material and Finish

Housing — UL94V-0, heat resistant resin, natural color

Contact — Copper alloy, 0.2µm min. gold plated on contact area, 0.1µm tin-lead plated or tin plated on soldering area, 1.3µm min. nickel underplated on entire contact, 0.1µm thick tin plated on grounding contact.



.5 mm FH Receptacle Assemblies

Positions	Height	Dimensions					Ground Contact	SIF-200	With Pickup Cap	Packaging Type	Part Number
		A	B	C	D	E					
120	4	29.50 1.161	36.80 1.449	3.25 .128	6.20 .244	6.00 .236	—	—	Yes	Tape	2-6473527-9
	12	29.50 1.161	36.80 1.449	11.25 .443	6.30 .248	6.50 .256	Yes	—	Yes	Hard Tray	6376618-1
160	12	39.50 1.555	46.80 1.843	11.25 .443	6.30 .248	6.50 .256	Yes	—	Yes	Tray	6-5353703-2
200	4	49.50 1.949	56.80 2.236	3.25 .128	6.20 .244	6.00 .236	—	—	Yes	Semi H/T	3-6565778-5
	8	49.50 1.949	56.80 2.236	7.25 .285	6.30 .248	6.50 .256	Yes	—	—	Hard Tray	6-5353699-5
220	4	54.50 2.146	61.80 2.433	3.25 .128	6.20 .244	6.00 .236	Yes	—	—	Hard Tray	3-6318490-6
	4	54.50 2.146	61.80 2.433	3.25 .128	6.20 .244	6.00 .236	Yes	—	Yes	Hard Tray	6-5353606-6
	8	54.50 2.146	61.80 2.433	7.25 .285	6.30 .248	6.50 .256	Yes	Yes	Yes	Hard Tray	6-5353700-5
240	4	59.50 2.343	66.80 2.630	3.25 .128	6.20 .244	6.00 .236	—	—	Yes	Hard Tray	3-6473884-7
	4	59.50 2.343	66.80 2.630	3.25 .128	6.20 .244	6.00 .236	Yes	—	Yes	Hard Tray	3-5353606-7

Note: Part Numbers are RoHS compliant.

0.5mm Free Height (FH) Connectors (Continued)


Receptacle Assembly with Bridge

**Acceptable Board Stacking
Height = 16mm**


Material and Finish

Housing — UL94V-0, heat resistant resin, natural color



Contact — Copper alloy, 0.2µm min. gold plated on contact area, 0.1µm tin-lead plated or tin plated on soldering area, 1.3µm min. nickel underplated on entire contact, 0.1µm thick tin plated on grounding contact.



Section Y-Y
(Grounding Position)



**Section X-X
(Signal Position)**



**PC Board Layout
(I = For Grounding Contact)**

.5 mm FH Receptacle Assemblies with Bridge

Positions	Height	Dimensions						Ground Contact	SIF-200	With Pickup Cap	Packaging Type	Part Number
		A	B	C	D	E	F					
240	4	29.50	36.80	3.25	37.80	6.20	6.00	Yes	—	Yes	Tape	5-6123675-9
		1.161	1.449	.128	1.488	.244	.236					
320	12	39.50	46.80	11.25	47.80	6.50	6.30	Yes	—	Yes	Hard Tray	6-5353649-2
		1.555	1.843	.443	1.882	.256	.248					
440	4	54.50	61.80	3.25	62.80	6.20	6.00	Yes	—	Yes	Hard Tray	3-1827231-6
		2.146	2.433	.128	2.472	.244	.236					

Note: Part Numbers are RoHS compliant.


0.5mm Free Height (FH) Connectors (Continued)

Plug Assembly

Material and Finish

Housing — UL94V-0, heat resistant resin, natural color

Contact — Copper alloy, 0.2µm min. gold plated on contact area, 0.1µm tin-lead plated or tin plated on soldering area, 1.3µm min. nickel underplated on entire contact, 0.1µm thick tin plated on grounding contact.



.5 mm FH Plug Assemblies

Positions	Height	Dimensions			Giga Ground Shield	SIF-200	With Pickup Cap	Packaging Type	Part Number
		A	B	C					
120	7	29.50 1.161	36.80 1.449	6.45 .254	—	—	Yes	Tape	2-6473530-9
	8	29.50 1.161	36.80 1.449	7.45 .293	—	—	—	Hard Tray	6376622-1
160	8	39.50 1.555	46.80 1.843	7.45 .293	Yes	Yes	Yes	Hard Tray	6-5353706-2
200	5	49.50 1.949	56.80 2.236	4.45 .1175	Yes	—	Yes	Semi H/T	3-6612148-5
	7	49.50 1.949	56.80 2.236	6.45 .254	Yes	—	—	Hard Tray	6-6123766-5
	8	49.50 1.949	56.80 2.236	7.45 .293	Yes	—	Yes	Semi H/T	3-6565779-5
220	5	54.50 2.146	61.80 2.433	4.45 .1175	Yes	—	—	Hard Tray	3-1827253-6
	8	54.50 2.146	61.80 2.433	7.45 .293	Yes	—	—	Hard Tray	3-6318491-6
240	6	59.50 2.343	66.80 2.630	5.45 .215	Yes	—	Yes	Hard Tray	3-5353614-7
	6	59.50 2.343	66.80 2.630	5.45 .215	—	—	Yes	Hard Tray	3-6473868-7

Note: Part Numbers are RoHS compliant.


0.5mm Free Height (FH) Connectors (Continued)

Plug Assembly with Bridge


Material and Finish

Housing — UL94V-0, heat resistant resin, natural color






Contact — Copper alloy, 0.2µm min. gold plated on contact area, 0.1µm tin-lead plated or tin plated on soldering area, 1.3µm min. nickel underplated on entire contact, 0.1µm thick tin plated on grounding contact.



**Section Y-Y
(Grounding Position)**



**Section X-X
(Signal Position)**



.5 mm FH Plug Assemblies with Bridge

Positions	Height	Dimensions				Giga Ground Shield	SIF-200	With Pickup Cap	Packaging Type	Part Number
		A	B	C	D					
240	5	29.50 1.161	36.80 1.449	4.45 .175	36.90 1.453	Yes	—	Yes	Tape	9-6123672-9
240	5	29.50 1.161	36.80 1.449	4.45 .175	36.90 1.453	Yes	—	Yes	Tape	5-6123672-9
320	8	39.50 1.555	46.80 1.843	7.45 .293	46.90 1.846	Yes	—	Yes	Hard Tray	6-5353652-2
440	5	54.50 2.146	61.80 2.433	4.45 .175	61.90 2.437	Yes	—	Yes	Hard Tray	3-1827233-6
440	8	54.50 2.146	61.80 2.433	7.45 .293	61.90 2.437	Yes	—	Yes	Hard Tray	3-5353652-6

Note: Part Numbers are RoHS compliant.

Engineering Notes